



Shurtape[®]

TRUE TO YOUR WORK[™]

2016-2017 PRODUCT CATALOG



Headquartered in Hickory, NC, Shurtape Technologies, LLC, is a privately owned, fifth generation, global corporation that designs, develops, manufactures and distributes pressure-sensitive tapes that make our customers' lives easier and help them do their jobs better.

We're an established company in continuous operation since 1880. We have a history of entrepreneurship and innovation, from spinning cotton, yarn and twine to making high-quality, high-performing tapes today.

Shurtape brand was introduced in 1955 when we began manufacturing tapes, with a focus on solutions for those with the highest, most exacting standards. Today, we proudly serve a variety of markets, from painting, packaging and arts & entertainment to HVAC, transportation and building & construction.

No matter the job, it's critical you're prepared. Shurtape has you covered with the tapes you trust - and the product features you demand - to deliver superior results.



**PROUDLY
APPLIED
SINCE
1955**





OUR MISSION

BE TRUE TO YOUR WORK

THE STICKY TRUTH

Not all packaging operations are created equal. The Sticky Truth serves as your guide to help identify potential case sealing issues, while providing you with the knowledge and resources to make better, more informed decisions to enhance your packaging operations. Get to know The Sticky Truth about packaging at ShurSEALSecure.com.

TAPE UNIVERSITY

Tape University is a leading online learning resource for all things tape. We're committed to building the best learning experience by providing the tape industry's most comprehensive place to learn about the past, present and future trends. See what's new – or ask your own tape-related questions – at TapeUniversity.com.

MISSION: HVAC

The trades face a worrisome future as Baby Boomers age out of the industry with few replacements to count on. That's why we're on a mission to educate for success. Through our Mission: HVAC program, we're following three students who are pursuing careers in the HVAC field to show the world just how rewarding – and fun – technical education can be. Follow the journey at TapeUniversity.com/MissionHVAC

MISSION: PACKAGING

Building upon the success of our Mission: HVAC program, our Mission: Packaging program is designed to enhance students' educational experiences within the packaging field. Each month, three students are given packaging-themed challenges that test their classroom learnings and real-life skills. And, like their HVAC counterparts, are rewarded for their hard work and completion of all 10 missions with \$5,000 to put toward the cost of their education. Learn more at TapeUniversity.com/MissionPackaging.

CONTENTS

MASKING & PAPER TAPES	2
Painter's Grade Masking - Specialty Dispenser	4
Painter's Grade Masking - Production	5
General Purpose Masking	6
Specialty Masking	6
High Performance Masking	7
Colored Crepe Paper	8
Colored Flatback Paper	8
Flatback Paper	9
PACKAGING SOLUTIONS	10
Hot Melt Carton Sealing	12
Hot Melt Specialty Carton Sealing	13
Hot Melt Printed Carton Sealing	14
Hot Melt Directly Printable Carton Sealing	14
Emulsion Acrylic Carton Sealing	15
Solvent-Based Acrylic Carton Sealing	16
Clear to the Core Packaging	16
Office & Specialty Packaging	17
Label Protection	17
Tensilized Strapping	18
Filament Strapping	19
Water Activated Paper	20
Manual Tape Application – Hand-Held	22
Manual Tape Application – Tabletop	23
Automated Tape Application	23
ShurSEAL® Packaging Solutions	24
CLOTH & DUCT TAPES	26
Co-Extruded Duct	28
ShurGRIP® Co-Extruded Duct	29
Colored & Printed Duct	30
Performance Duct	31
Heavy Duty Duct	32
Super Performance Duct	32
Specialty Performance Duct	33
Coated Cloth	34
Stucco Masking	36
FOIL & FILM TAPES	38
UL 181B-FX Listed	40
Roll Mastic	40
Cold Temperature Foils	41
UL 181A-P/B-FX Listed	41
Aluminum & Paper Composite	42
Specialty Tapes	42
PVC Film	43
DOUBLE-COATED TAPES	44
Double-Coated Paper	46
Double-Coated Film	47
Double-Coated Cloth	47
Transfer Adhesive	48
Dispenser	48
PRODUCT INNOVATIONS	49
APPLICABLE STANDARDS	50
LOCATIONS	50
PRODUCT INDEX	51
WARRANTY	51

MASKING & PAPER TAPES



WE KNOW YOUR TIME IS VALUABLE. THAT'S WHY OUR MASKING AND PAPER TAPES ARE ENGINEERED TO MEET THE DEMANDS OF A RANGE OF JOBS. WHETHER YOU REQUIRE TENSILE STRENGTH, TEMPERATURE RESISTANCE, REMOVABILITY, FLEXIBILITY OR SHARP PAINT LINES, **SHURTAPE DELIVERS.**

PAINTER'S GRADE MASKING – SPECIALTY

FROGTAPE®



**PROFESSIONAL GRADE
MEDIUM ADHESION
RUBBER-BASED ADHESIVE
EXCLUSIVE PAINTBLOCK® TECHNOLOGY**

TENSILE (LBS/IN WIDTH)	22
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	30
THICKNESS (MILS)	5.7
ELONGATION (%)	10
MAXIMUM SERVICE TEMPERATURE (°F)	-
APPLICABLE STANDARDS*	12

For interior or exterior use on multiple surfaces, including cured painted walls, wood trim, glass and metal; Withstands direct sunlight for up to 7 days.



CP 27®



**PREMIUM GRADE
MEDIUM ADHESION
SYNTHETIC RUBBER-BASED ADHESIVE**

TENSILE (LBS/IN WIDTH)	24
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	32
THICKNESS (MILS)	5.3
ELONGATION (%)	8
MAXIMUM SERVICE TEMPERATURE (°F)	200
APPLICABLE STANDARDS*	-

For interior and exterior use on multiple surfaces, including painted walls, glass, vinyl, metal and wood; Not recommended for use on wallpaper, unpainted wallboard, ceiling tile or with uncured coatings.



CP 150



**PAINTER'S MATE GREEN®
MEDIUM ADHESION
RUBBER-BASED ADHESIVE**

TENSILE (LBS/IN WIDTH)	14
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	29
THICKNESS (MILS)	5.4
ELONGATION (%)	12
MAXIMUM SERVICE TEMPERATURE (°F)	150
APPLICABLE STANDARDS*	12

For interior use on painted walls, woodwork, glass, metal and vinyl.



CP 60®



**PREMIUM GRADE, RAZOREDGE®
LOW ADHESION
ACRYLIC-BASED ADHESIVE**

TENSILE (LBS/IN WIDTH)	23
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	14
THICKNESS (MILS)	3.6
ELONGATION (%)	4.5
MAXIMUM SERVICE TEMPERATURE (°F)	-
APPLICABLE STANDARDS*	-

For painting stripes, diamonds and other patterns on walls; For interior use on delicate surfaces such as painted drywall and faux finishes.



DISPENSER

EM 101



**HAND-HELD PAINT MASKING TOOL
DUAL-SHARPENED BLADE
HOLDS A VARIETY OF TAPE WIDTHS**

For surface preparation prior to interior and exterior paint jobs; Applies painter's tape and masking film or paper simultaneously.

RECOMMENDED PRODUCTS
CP 27



PAINTER'S GRADE MASKING – PRODUCTION

COLONIAL®



**PREMIUM GRADE
HIGH ADHESION
RUBBER-BASED ADHESIVE**

TENSILE (LBS/IN WIDTH)	24
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	39
THICKNESS (MILS)	6.4
ELONGATION (%)	9
MAXIMUM SERVICE TEMPERATURE (°F)	200
APPLICABLE STANDARDS*	12

For industrial and automotive paint applications that do not require the use of a bake oven; Can also be used for general purpose masking applications that demand a premium performance tape.

CP 66®



**CONTRACTOR GRADE
HIGH ADHESION
RUBBER-BASED ADHESIVE**

TENSILE (LBS/IN WIDTH)	23
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	38
THICKNESS (MILS)	5.6
ELONGATION (%)	8
MAXIMUM SERVICE TEMPERATURE (°F)	150
APPLICABLE STANDARDS*	12

For residential and commercial painting and construction, industrial masking, holding and packaging; Use in applications that demand quick stick and conformability to irregularly shaped surfaces.

CP 102



**INDUSTRIAL GRADE
MEDIUM-HIGH ADHESION
RUBBER-BASED ADHESIVE**

TENSILE (LBS/IN WIDTH)	19
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	32
THICKNESS (MILS)	5.4
ELONGATION (%)	9
MAXIMUM SERVICE TEMPERATURE (°F)	200
APPLICABLE STANDARDS*	12

For the industrial, commercial and residential paint markets for use on vinyl, metal, glass, plastic and rubber.

CP 107



**INDUSTRIAL GRADE
MEDIUM-HIGH ADHESION
SYNTHETIC RUBBER-BASED ADHESIVE**

TENSILE (LBS/IN WIDTH)	19
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	32
THICKNESS (MILS)	4.9
ELONGATION (%)	9
MAXIMUM SERVICE TEMPERATURE (°F)	150
APPLICABLE STANDARDS*	12

For non-critical painting and industrial applications that demand good adhesion, quick stick and clean removal; Also used for general purpose packaging, bundling, holding, splicing and tabbing; For use on vinyl, glass, plastic and rubber.



GENERAL PURPOSE MASKING

CP 83



UTILITY GRADE
HIGH ADHESION
SYNTHETIC RUBBER-BASED ADHESIVE

TENSILE (LBS/IN WIDTH)	20
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	49
THICKNESS (MILS)	5.0
ELONGATION (%)	8
MAXIMUM SERVICE TEMPERATURE (°F)	150
APPLICABLE STANDARDS*	12

For general purpose packaging, bundling, holding, splicing, tabbing and banding applications involving a variety of substrates; Not recommended for exacting industrial masking, spray painting or oven baking applications.

CP 101



GENERAL PURPOSE GRADE
MEDIUM-HIGH ADHESION
BLENDED RUBBER-BASED ADHESIVE

TENSILE (LBS/IN WIDTH)	18
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	35
THICKNESS (MILS)	4.9
ELONGATION (%)	9.5
MAXIMUM SERVICE TEMPERATURE (°F)	150
APPLICABLE STANDARDS*	12

For bundling, packaging, holding, splicing, masking and labeling for home, school and industry.

CP 105



GENERAL PURPOSE GRADE
MEDIUM-HIGH ADHESION
SYNTHETIC RUBBER-BASED ADHESIVE

TENSILE (LBS/IN WIDTH)	18
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	30
THICKNESS (MILS)	4.6
ELONGATION (%)	7
MAXIMUM SERVICE TEMPERATURE (°F)	150
APPLICABLE STANDARDS*	12

For non-critical bundling and labeling applications; Also used for general purpose packaging, holding and splicing applications for home, school and industry.

HIGH PERFORMANCE MASKING

CP 905



HIGH PERFORMANCE GRADE
HIGH-TEMPERATURE
EXCELLENT ADHESION
RUBBER-BASED ADHESIVE

TENSILE (LBS/IN WIDTH)	24
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	41
THICKNESS (MILS)	6.4
ELONGATION (%)	11
MAXIMUM SERVICE TEMPERATURE (°F)	350
APPLICABLE STANDARDS*	12

For high-temperature - up to 350 F - paint masking and metal fabrication applications in the transportation (auto, coaches, buses and marine) industry; Recommended for indoor use only.

CF 740



HIGH PERFORMANCE GRADE
HIGH-TEMPERATURE
MEDIUM-HIGH ADHESION
RUBBER-BASED ADHESIVE

TENSILE (LBS/IN WIDTH)	25
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	39
THICKNESS (MILS)	6.3
ELONGATION (%)	11
MAXIMUM SERVICE TEMPERATURE (°F)	350
APPLICABLE STANDARDS*	12

For high-temperature, demanding industrial paint masking applications in the transportation (auto, coaches, buses and marine) and metal fabrication industries; Also used for EPDM rubber insulation protection; Recommended for indoor use only.

CP 650



HIGH PERFORMANCE GRADE
HIGH-TEMPERATURE
MEDIUM-HIGH ADHESION
RUBBER-BASED ADHESIVE

TENSILE (LBS/IN WIDTH)	28
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	37
THICKNESS (MILS)	6.6
ELONGATION (%)	11
MAXIMUM SERVICE TEMPERATURE (°F)	325
APPLICABLE STANDARDS*	1, 12

For demanding, high-temperature paint masking and metal fabrication applications in the transportation (auto, coaches, buses and marine) industry; Also used for metal preparation, painting, coating and gel coat masking; Recommended for indoor use only.

SPECIALTY MASKING

CP 743



SPECIALTY GRADE
PHOTOGRAPHIC BLACK
VERY HIGH ADHESION
RUBBER-BASED ADHESIVE

TENSILE (LBS/IN WIDTH)	24
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	47
THICKNESS (MILS)	6.5
ELONGATION (%)	8
MAXIMUM SERVICE TEMPERATURE (°F)	150
APPLICABLE STANDARDS*	12

For use in photo studios, film processing labs and home darkrooms; Recommended for use as a chart tape; Used for quality photographic reproduction work, including cropping and edging negatives for contact printing; Also used for sealing camera bellows and film holders against light leaks.

PE 100



FLOORMATE®
LOW ADHESION
ACRYLIC-BASED ADHESIVE

TENSILE (LBS/IN WIDTH)	11
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	15
THICKNESS (MILS)	4.6
ELONGATION (%)	500
MAXIMUM SERVICE TEMPERATURE (°F)	160
APPLICABLE STANDARDS*	-

For temporary use on properly prepared and cured wood floors; Also used as a gym floor marking tape for creating temporary lines and boundaries; Can also be used on other hard flooring surfaces, including sheet vinyl, wood laminates, engineered hardwood, tile, marble and granite.



CP 500



HIGH PERFORMANCE GRADE
HIGH-TEMPERATURE
MEDIUM-HIGH ADHESION
RUBBER-BASED ADHESIVE

TENSILE (LBS/IN WIDTH)	26
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	43
THICKNESS (MILS)	5.8
ELONGATION (%)	9
MAXIMUM SERVICE TEMPERATURE (°F)	300
APPLICABLE STANDARDS*	12

For high-temperature paint masking and metal fabrication applications in the transportation (auto, coaches, buses and marine) industry; Also used for wet sanding applications; Recommended for indoor use only.

CP 450



HIGH PERFORMANCE GRADE
MODERATE-TEMPERATURE
MEDIUM-HIGH ADHESION
RUBBER-BASED ADHESIVE

TENSILE (LBS/IN WIDTH)	31
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	37
THICKNESS (MILS)	6.9
ELONGATION (%)	10
MAXIMUM SERVICE TEMPERATURE (°F)	225
APPLICABLE STANDARDS*	12

For moderate-temperature, demanding paint masking applications in the transportation (auto, coaches, buses and marine) and metal fabrication industries; Also used for wet sanding applications; Recommended for indoor use only.

CP 400



HIGH PERFORMANCE GRADE
MODERATE-TEMPERATURE
MEDIUM-HIGH ADHESION
RUBBER-BASED ADHESIVE

TENSILE (LBS/IN WIDTH)	24
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	34
THICKNESS (MILS)	5.7
ELONGATION (%)	10
MAXIMUM SERVICE TEMPERATURE (°F)	200
APPLICABLE STANDARDS*	12

For moderate-temperature paint masking and metal fabrication applications in the transportation (auto, coaches, buses and marine) industry; Recommended for indoor use only.

COLORED CREPE PAPER

CP 631



**GENERAL PURPOSE GRADE
MEDIUM-HIGH ADHESION
SYNTHETIC RUBBER-BASED ADHESIVE**

TENSILE (LBS/IN WIDTH)	20
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	34
THICKNESS (MILS)	4.9
ELONGATION (%)	9
MAXIMUM SERVICE TEMPERATURE (*F)	150
APPLICABLE STANDARDS*	5, 12

For general purpose labeling, color-coding, decorating and identification; Can also be used for packaging, bundling, binding, holding, splicing and banding applications.



COLORED FLATBACK PAPER

FP 17



**PRINTABLE, LOW TEMPERATURE
HIGH ADHESION
RUBBER-BASED ADHESIVE**

TENSILE (LBS/IN WIDTH)	30
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	52
THICKNESS (MILS)	5.4
ELONGATION (%)	3
MAXIMUM SERVICE TEMPERATURE (*F)	150
APPLICABLE STANDARDS*	13

For general purpose packaging, bundling, holding, binding, splicing, labeling, color-coding, banding, decorating and identification.

FP 227



**PRINTABLE
HIGH ADHESION
RUBBER-BASED ADHESIVE**

TENSILE (LBS/IN WIDTH)	30
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	57
THICKNESS (MILS)	5.8
ELONGATION (%)	2.5
MAXIMUM SERVICE TEMPERATURE (*F)	150
APPLICABLE STANDARDS*	5, 13

For full-web flexographic printing equipment or hand-labeling applications.

**Fluorescent colors do not conform to ASTM D-4236



FLATBACK PAPER

FP 115



**HIGH PERFORMANCE GRADE
REINFORCED FLATBACK PAPER
VERY HIGH ADHESION
SYNTHETIC RUBBER-BASED ADHESIVE**

TENSILE (LBS/IN WIDTH)	40
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	70
THICKNESS (MILS)	6.5
ELONGATION (%)	3
MAXIMUM SERVICE TEMPERATURE (*F)	120
APPLICABLE STANDARDS*	13

For industrial splicing, start-up, tabbing, shingling and overlapping applications; Effectively secures the paper to the core during roll start-up, holds the splice during processing and anchors the end of the roll securely.



FP 726



**PRINTABLE, HIGH-STRENGTH
HIGH ADHESION
RUBBER-BASED ADHESIVE**

TENSILE (LBS/IN WIDTH)	45
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	72
THICKNESS (MILS)	6.6
ELONGATION (%)	3
MAXIMUM SERVICE TEMPERATURE (*F)	150
APPLICABLE STANDARDS*	5, 13

For identification labeling, color-coding, packaging closure and other applications where printing is necessary.



FP 202



**PACKAGING PREMIUM GRADE
HEAVY DUTY, BLEACHED KRAFT PAPER
VERY HIGH ADHESION
RUBBER-BASED ADHESIVE**

TENSILE (LBS/IN WIDTH)	55
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	63
THICKNESS (MILS)	7.5
ELONGATION (%)	3
MAXIMUM SERVICE TEMPERATURE (*F)	180
APPLICABLE STANDARDS*	11, 13

For splicing various substrates; Used for heavy duty hand and machine carton sealing applications; Used for general purpose applications where a thick, flatback paper tape is required.

FP 96



**PACKAGING GRADE
KRAFT FLATBACK PAPER
VERY HIGH ADHESION
RUBBER-BASED ADHESIVE**

TENSILE (LBS/IN WIDTH)	36
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	90
THICKNESS (MILS)	6.1
ELONGATION (%)	6
MAXIMUM SERVICE TEMPERATURE (*F)	150
APPLICABLE STANDARDS*	13

For hand and machine carton sealing; Used for splicing various substrates; Also used for general purpose packaging, binding, holding, tabbing, reinforcing, banding and patching applications.

FP 97



**GENERAL PURPOSE GRADE
KRAFT FLATBACK PAPER
VERY HIGH ADHESION
SYNTHETIC RUBBER-BASED ADHESIVE**

TENSILE (LBS/IN WIDTH)	35
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	110
THICKNESS (MILS)	6.0
ELONGATION (%)	6
MAXIMUM SERVICE TEMPERATURE (*F)	150
APPLICABLE STANDARDS*	13, 24, 25, 26, 27

For hand and machine carton sealing; Used for splicing various substrates; Also used for general purpose packaging, binding, holding, tabbing, reinforcing, banding, patching and floor seaming applications; FDA compliant.

PACKAGING SOLUTIONS

WE KNOW EVERY SEALING SITUATION IS UNIQUE. AND WE UNDERSTAND THAT KEEPING YOUR LINES RUNNING AT PEAK PRODUCTION, WHILE PRODUCING A BETTER, MORE RELIABLE CASE SEAL IS A PRIORITY. THAT'S WHY WE TOOK A HOLISTIC APPROACH IN THE DEVELOPMENT OF OUR TAPE AND TAPE APPLICATION TECHNOLOGIES TO DELIVER SOLUTIONS THAT ARE PURPOSE-BUILT FOR YOUR PACKAGING AND CASE SEALING OPERATIONS. NO MATTER THE APPLICATION, WE DELIVER **SECURE SEALS, EVERY TIME.**

4P PrimeLoc



FOR MORE
INFORMATION

Shurtape

ShurSEALSecure.com

**ShurSEAL
SOLUTION**

1.888.442.TAPE

7300

HOT MELT CARTON SEALING

HP 100®



**GENERAL PURPOSE GRADE
25 MICRON CAST BOPP FILM
SYNTHETIC HOT MELT ADHESIVE**

TENSILE (LBS/IN WIDTH) (LONGITUDINAL)	21
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	43
HOLDING POWER TO FIBERBOARD (MINUTES)	10,000
THICKNESS (MILS)	1.6
ELONGATION (%)	150
APPLICATION TEMPERATURE RANGE (°F)	35 - 110
SERVICE TEMPERATURE RANGE (°F)	-20 - 150
APPLICABLE STANDARDS*	18, 25, 28

For manual or automated industrial carton sealing of lightweight cartons with minimal exposure to handling, shipping and load stress.

HP 200®



**PRODUCTION GRADE
30 MICRON CAST BOPP FILM
SYNTHETIC HOT MELT ADHESIVE**

TENSILE (LBS/IN WIDTH) (LONGITUDINAL)	27
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	44
HOLDING POWER TO FIBERBOARD (MINUTES)	15,000
THICKNESS (MILS)	1.9
ELONGATION (%)	150
APPLICATION TEMPERATURE RANGE (°F)	35 - 110
SERVICE TEMPERATURE RANGE (°F)	-20 - 150
APPLICABLE STANDARDS*	4, 18, 25, 28

For manual or automated industrial carton sealing of medium-weight cartons in normal manufacturing and shipping environments.

**White not compliant with standards 25, 28

HP 300®



**PERFORMANCE GRADE
35 MICRON CAST BOPP FILM
SYNTHETIC HOT MELT ADHESIVE**

TENSILE (LBS/IN WIDTH) (LONGITUDINAL)	30
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	47
HOLDING POWER TO FIBERBOARD (MINUTES)	20,000
THICKNESS (MILS)	2.2
ELONGATION (%)	150
APPLICATION TEMPERATURE RANGE (°F)	35 - 110
SERVICE TEMPERATURE RANGE (°F)	-20 - 150
APPLICABLE STANDARDS*	4, 18, 25, 28

For critical closure manual or automated industrial carton sealing of medium-weight cartons that are subjected to increased handling stress.

HP 400®



**HIGH PERFORMANCE GRADE
40 MICRON CAST BOPP FILM
SYNTHETIC HOT MELT ADHESIVE**

TENSILE (LBS/IN WIDTH) (LONGITUDINAL)	33
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	54
HOLDING POWER TO FIBERBOARD (MINUTES)	25,000
THICKNESS (MILS)	2.5
ELONGATION (%)	150
APPLICATION TEMPERATURE RANGE (°F)	35 - 110
SERVICE TEMPERATURE RANGE (°F)	-20 - 150
APPLICABLE STANDARDS*	4, 9, 18, 25, 28

For manual or automated industrial carton sealing of large, bulky or heavy content cartons; For use in higher speed, critical closure applications; Can be used in moderate to severe handling environments.

HP 500®



**HEAVY DUTY GRADE
50 MICRON CAST BOPP FILM
SYNTHETIC HOT MELT ADHESIVE**

TENSILE (LBS/IN WIDTH) (LONGITUDINAL)	42
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	58
HOLDING POWER TO FIBERBOARD (MINUTES)	30,000
THICKNESS (MILS)	3.0
ELONGATION (%)	150
APPLICATION TEMPERATURE RANGE (°F)	35 - 110
SERVICE TEMPERATURE RANGE (°F)	-20 - 150
APPLICABLE STANDARDS*	4, 9, 18, 25, 28

For manual or automated industrial carton sealing of heavy, bulky cartons, including overstuffed or under-filled cartons, in high stress and extreme handling conditions.

HP 800



**HEAVY DUTY GRADE
50 MICRON POLYESTER FILM
SYNTHETIC HOT MELT ADHESIVE**

TENSILE (LBS/IN WIDTH) (LONGITUDINAL)	54
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	95
HOLDING POWER TO FIBERBOARD (MINUTES)	35,000
THICKNESS (MILS)	3.4
ELONGATION (%)	130
APPLICATION TEMPERATURE RANGE (°F)	35 - 110
SERVICE TEMPERATURE RANGE (°F)	-20 - 150
APPLICABLE STANDARDS*	4, 7, 8, 18, 25, 29

For manual or automated industrial carton sealing of heavy duty, critical closure cartons, including military supplies, high-value electronic components and hazardous materials and chemicals.

HOT MELT SPECIALTY CARTON SEALING

HP 132®



**COLD ENVIRONMENT
GENERAL PURPOSE GRADE
25 MICRON CAST BOPP FILM
SYNTHETIC HOT MELT ADHESIVE**

TENSILE (LBS/IN WIDTH) (LONGITUDINAL)	21
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	30
HOLDING POWER TO FIBERBOARD (MINUTES)	10,000
THICKNESS (MILS)	1.6
ELONGATION (%)	150
APPLICATION TEMPERATURE RANGE (°F)	20 - 75
SERVICE TEMPERATURE RANGE (°F)	-20 - 100
APPLICABLE STANDARDS*	18, 25, 28

For manual or automated industrial sealing of lightweight cartons in cold temperature environments such as food processing and packaging facilities, as well as in cold weather moving/storage and unheated warehouses.

HP 232®



**COLD ENVIRONMENT
PRODUCTION GRADE
30 MICRON CAST BOPP FILM
SYNTHETIC HOT MELT ADHESIVE**

TENSILE (LBS/IN WIDTH) (LONGITUDINAL)	27
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	30
HOLDING POWER TO FIBERBOARD (MINUTES)	10,000
THICKNESS (MILS)	1.9
ELONGATION (%)	150
APPLICATION TEMPERATURE RANGE (°F)	20 - 75
SERVICE TEMPERATURE RANGE (°F)	-20 - 100
APPLICABLE STANDARDS*	18, 25, 28

For manual or automated industrial sealing of medium-weight cartons in cold temperature environments such as food processing and packaging facilities, as well as in cold weather moving/storage and unheated warehouses.

HP 235



**RECYCLED CARTONS
PRODUCTION GRADE
30 MICRON CAST BOPP FILM
SYNTHETIC HOT MELT ADHESIVE**

TENSILE (LBS/IN WIDTH) (LONGITUDINAL)	27
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	50
HOLDING POWER TO FIBERBOARD (MINUTES)	15,000
THICKNESS (MILS)	2.0
ELONGATION (%)	150
APPLICATION TEMPERATURE RANGE (°F)	35 - 110
SERVICE TEMPERATURE RANGE (°F)	-20 - 150
APPLICABLE STANDARDS*	4, 18, 25, 28

For manual and automated industrial sealing of medium-weight, highly recycled cartons, particularly 100 percent recycled.



HOT MELT PRINTED CARTON SEALING

HP 240



**PRODUCTION GRADE
STANDARD MESSAGE PRINT
30 MICRON CAST BOPP FILM
SYNTHETIC HOT MELT ADHESIVE**

TENSILE (LBS/IN WIDTH) (LONGITUDINAL)	27
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	44
HOLDING POWER TO FIBERBOARD (MINUTES)	15,000
THICKNESS (MILS)	1.9
ELONGATION (%)	150
APPLICATION TEMPERATURE RANGE (°F)	35 - 110
SERVICE TEMPERATURE RANGE (°F)	-20 - 150
APPLICABLE STANDARDS*	4, 18, 25, 28

Printed with standard messages to prevent pilferage or inform handlers of care; For manual or automated industrial carton sealing of medium-weight cartons in normal manufacturing and shipping environments.

HP 250



**PRODUCTION GRADE
CUSTOM PRINT
30 MICRON CAST BOPP FILM
SYNTHETIC HOT MELT ADHESIVE**

TENSILE (LBS/IN WIDTH) (LONGITUDINAL)	27
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	44
HOLDING POWER TO FIBERBOARD (MINUTES)	15,000
THICKNESS (MILS)	1.9
ELONGATION (%)	150
APPLICATION TEMPERATURE RANGE (°F)	35 - 110
SERVICE TEMPERATURE RANGE (°F)	-20 - 150
APPLICABLE STANDARDS*	4, 18, 25

Custom-printed to prevent pilferage and allow personalization of outgoing cartons; For manual or automated industrial carton sealing of medium-weight cartons in normal manufacturing and shipping environments.

HOT MELT DIRECTLY PRINTABLE CARTON SEALING

HP 260



**PRODUCTION GRADE
30 MICRON CAST BOPP FILM
SYNTHETIC HOT MELT ADHESIVE**

TENSILE (LBS/IN WIDTH) (LONGITUDINAL)	27
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	44
HOLDING POWER TO FIBERBOARD (MINUTES)	15,000
THICKNESS (MILS)	1.9
ELONGATION (%)	150
APPLICATION TEMPERATURE RANGE (°F)	35 - 110
SERVICE TEMPERATURE RANGE (°F)	-20 - 150
APPLICABLE STANDARDS*	4, 18

For use on Siat L33, L36, L233 (or equivalent) surface printing presses; For manual sealing of medium-weight cartons in normal manufacturing and shipping environments; May also be used in automated industrial carton sealing applications.

HP 460



**HIGH PERFORMANCE GRADE
40 MICRON CAST BOPP FILM
SYNTHETIC HOT MELT ADHESIVE**

TENSILE (LBS/IN WIDTH) (LONGITUDINAL)	33
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	54
HOLDING POWER TO FIBERBOARD (MINUTES)	25,000
THICKNESS (MILS)	2.5
ELONGATION (%)	150
APPLICATION TEMPERATURE RANGE (°F)	35 - 110
SERVICE TEMPERATURE RANGE (°F)	-20 - 150
APPLICABLE STANDARDS*	4, 18

For use on Siat L33, L36, L233 (or equivalent) surface printing presses; For manual or automated industrial carton sealing of large, bulky or heavy content cartons; For use in higher speed, critical closure applications; For use in moderate to severe handling environments.

HP 560



**HEAVY DUTY GRADE
50 MICRON CAST BOPP FILM
SYNTHETIC HOT MELT ADHESIVE**

TENSILE (LBS/IN WIDTH) (LONGITUDINAL)	42
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	58
HOLDING POWER TO FIBERBOARD (MINUTES)	30,000
THICKNESS (MILS)	3.0
ELONGATION (%)	150
APPLICATION TEMPERATURE RANGE (°F)	35 - 110
SERVICE TEMPERATURE RANGE (°F)	-20 - 150
APPLICABLE STANDARDS*	4, 9, 18

For use on Siat L33, L36, L233 (or equivalent) surface printing presses; For manual or automated industrial carton sealing of heavy, bulky cartons, including overstuffed or under-filled cartons, in high stress and extreme handling conditions.

GS 496



**PRODUCTION GRADE
CAST BOPP FILM
SYNTHETIC HOT MELT ADHESIVE
FIBERGLASS REINFORCED**

TENSILE (LBS/IN WIDTH)	100
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	70
THICKNESS (MILS)	4.5
ELONGATION (%)	3.7
SERVICE TEMPERATURE RANGE (°F)	-10 - 150
APPLICABLE STANDARDS*	-

For use on Siat L33, L36, L233 (or equivalent) surface printing presses; For general purpose strapping, packaging, bundling and palletizing applications.

EMULSION ACRYLIC CARTON SEALING

AP 101®



**GENERAL PURPOSE GRADE
25 MICRON CAST BOPP FILM
EMULSION ACRYLIC ADHESIVE**

TENSILE (LBS/IN WIDTH)	20
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	18
THICKNESS (MILS)	1.6
ELONGATION (%)	150
APPLICATION TEMPERATURE RANGE (°F)	20 - 110
SERVICE TEMPERATURE RANGE (°F)	-20 - 180
APPLICABLE STANDARDS*	25, 28

For non-critical closure of lightweight cartons in manual and automated industrial sealing settings.

**Tan not compliant with standards 25, 28



AP 180®



**PRODUCTION GRADE
25 MICRON CAST BOPP FILM
EMULSION ACRYLIC ADHESIVE**

TENSILE (LBS/IN WIDTH)	20
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	21
THICKNESS (MILS)	1.8
ELONGATION (%)	150
APPLICATION TEMPERATURE RANGE (°F)	20 - 110
SERVICE TEMPERATURE RANGE (°F)	-20 - 180
APPLICABLE STANDARDS*	25, 28

For manual and automated industrial sealing of lightweight cartons.

**Tan not compliant with standards 25, 28



AP 201®



**PRODUCTION GRADE
28 MICRON CAST BOPP FILM
EMULSION ACRYLIC ADHESIVE**

TENSILE (LBS/IN WIDTH)	24
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	22
THICKNESS (MILS)	2.0
ELONGATION (%)	150
APPLICATION TEMPERATURE RANGE (°F)	20 - 110
SERVICE TEMPERATURE RANGE (°F)	-20 - 180
APPLICABLE STANDARDS*	25, 28

For manual and automated industrial sealing of light-to-medium-weight cartons.

**Tan not compliant with standards 25, 28



AP 301®



**PERFORMANCE GRADE
35 MICRON CAST BOPP FILM
EMULSION ACRYLIC ADHESIVE**

TENSILE (LBS/IN WIDTH)	27
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	25
THICKNESS (MILS)	2.2
ELONGATION (%)	150
APPLICATION TEMPERATURE RANGE (°F)	20 - 110
SERVICE TEMPERATURE RANGE (°F)	-20 - 180
APPLICABLE STANDARDS*	25, 28

For manual and automated industrial sealing of medium-weight cartons in extreme temperature environments or subjected to handling stress.

**Tan not compliant with standards 25, 28



AP 401®



**HIGH PERFORMANCE GRADE
40 MICRON CAST BOPP FILM
EMULSION ACRYLIC ADHESIVE**

TENSILE (LBS/IN WIDTH)	30
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	27
THICKNESS (MILS)	2.5
ELONGATION (%)	150
APPLICATION TEMPERATURE RANGE (°F)	20 - 110
SERVICE TEMPERATURE RANGE (°F)	-20 - 180
APPLICABLE STANDARDS*	25, 28

For heavy duty manual and automated industrial sealing of cartons exposed to rough handling and load stress; Also used for critical closure of bulky packages.

**Tan not compliant with standards 25, 28



SOLVENT-BASED ACRYLIC CARTON SEALING

PP 802



**PREMIUM PLUS GRADE
25 MICRON CAST BOPP FILM
SOLVENT-BASED ACRYLIC ADHESIVE**

TENSILE (LBS/IN WIDTH)	22
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	25
THICKNESS (MILS)	2.0
ELONGATION (%)	140
APPLICATION TEMPERATURE RANGE (°F)	20 - 110
SERVICE TEMPERATURE RANGE (°F)	-20 - 180
APPLICABLE STANDARDS*	18

For light duty sealing, repairing and bundling of corrugated cartons, paper and film containers; Use with a hand-held or machine dispenser.

PP 810



**PREMIUM GRADE
25 MICRON CAST BOPP FILM
SOLVENT-BASED ACRYLIC ADHESIVE**

TENSILE (LBS/IN WIDTH)	22
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	22
THICKNESS (MILS)	1.8
ELONGATION (%)	140
APPLICATION TEMPERATURE RANGE (°F)	20 - 110
SERVICE TEMPERATURE RANGE (°F)	-20 - 180
APPLICABLE STANDARDS*	18

For sealing light- to medium-weight cartons in everyday shipping and handling environments; Also used for bundling and securing loose objects; Can also be used to repair corrugated cartons, paper and film containers; Use with a hand-held dispenser.

CLEAR TO THE CORE PACKAGING

PP 803



**PREMIUM PLUS GRADE
30 MICRON CAST BOPP FILM
SOLVENT-BASED ACRYLIC ADHESIVE**

TENSILE (LBS/IN WIDTH)	25
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	25
THICKNESS (MILS)	2.2
ELONGATION (%)	150
APPLICATION TEMPERATURE RANGE (°F)	20 - 110
SERVICE TEMPERATURE RANGE (°F)	-20 - 180
APPLICABLE STANDARDS*	18

For overlamination, label protection and carton closure applications that demand 100 percent clarity; For use in a broad range of temperatures.

PP 815



**HEAVY DUTY GRADE
40 MICRON CAST BOPP FILM
SOLVENT-BASED ACRYLIC ADHESIVE**

TENSILE (LBS/IN WIDTH)	26
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	28
THICKNESS (MILS)	2.6
ELONGATION (%)	140
APPLICATION TEMPERATURE RANGE (°F)	20 - 110
SERVICE TEMPERATURE RANGE (°F)	-20 - 180
APPLICABLE STANDARDS*	18

For critical sealing and repairing of corrugated containers in hot and cold environments; Use with a hand-held dispenser.



JLAR



**SPECIALTY GRADE
BOPP FILM
SOLVENT-BASED ACRYLIC ADHESIVE**

TENSILE (LBS/IN WIDTH)	24
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	30
THICKNESS (MILS)	2.6
ELONGATION (%)	140
APPLICATION TEMPERATURE RANGE (°F)	20 - 110
SERVICE TEMPERATURE RANGE (°F)	-20 - 180
APPLICABLE STANDARDS*	-

For overlamination and label protection applications that demand a clear to the core tape; Also used for light duty packaging, paper repair and mending, and holding applications; Recommended for use with counter and desk dispensers.

OFFICE & SPECIALTY PACKAGING

CT 109



**GENERAL PURPOSE GRADE
CELLULOSE FILM
STATIC-FREE
RUBBER-BASED ADHESIVE**

TENSILE (LBS/IN WIDTH)	22
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	35
THICKNESS (MILS)	1.7
ELONGATION (%)	18
MAXIMUM SERVICE TEMPERATURE (°F)	265
APPLICABLE STANDARDS*	16

For sealing, packaging and mending applications, particularly involving hard-to-stick-to surfaces; Also used for splicing applications.

VF 719



**ECONOMY GRADE
PRINTABLE UPVC FILM
NATURAL RUBBER ADHESIVE**

TENSILE (LBS/IN WIDTH)	23
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	13
THICKNESS (MILS)	1.9
ELONGATION (%)	60
MAXIMUM SERVICE TEMPERATURE (°F)	150
APPLICABLE STANDARDS*	20

For use with a hand dispenser to seal cartons with recycled fiber content, heavy ink coverage or rough surfaces.

LABEL PROTECTION

AP 15



**SHIPPING GRADE
25 MICRON CAST BOPP FILM
EMULSION ACRYLIC ADHESIVE**

TENSILE (LBS/IN WIDTH)	20
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	19
THICKNESS (MILS)	1.6
ELONGATION (%)	150
APPLICATION TEMPERATURE RANGE (°F)	20 - 110
SERVICE TEMPERATURE RANGE (°F)	-20 - 180
APPLICABLE STANDARDS*	25

For protecting shipping labels and other printed surfaces against weather and handling.



PP 808



**GENERAL PURPOSE GRADE
UPVC FILM
NATURAL RUBBER ADHESIVE**

TENSILE (LBS/IN WIDTH)	27
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	24
THICKNESS (MILS)	2.1
ELONGATION (%)	60
MAXIMUM SERVICE TEMPERATURE (°F)	150
APPLICABLE STANDARDS*	-

For lightweight bag sealing, banding, bundling and packaging applications; Also used for color-coding tasks.



PP 807



**PREMIUM GRADE
25 MICRON CAST BOPP FILM
SOLVENT-BASED ACRYLIC ADHESIVE**

TENSILE (LBS/IN WIDTH)	20
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	23
THICKNESS (MILS)	1.8
ELONGATION (%)	140
APPLICATION TEMPERATURE RANGE (°F)	20 - 110
SERVICE TEMPERATURE RANGE (°F)	-20 - 180
APPLICABLE STANDARDS*	-

For moisture-proof protection of labels and handling instructions; Also used for industrial and production laminating, joining, covering and protecting jobs.

TENSILIZED STRAPPING

PS 748



UTILITY GRADE
TENSILIZED, MOPP FILM
EMULSION ACRYLIC ADHESIVE

TENSILE (LBS/IN WIDTH)	100
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	34
THICKNESS (MILS)	2.8
ELONGATION (%)	30
SERVICE TEMPERATURE RANGE (°F)	0 - 250
APPLICABLE STANDARDS*	-

For light duty strapping, packaging, bundling and palletizing applications.

PS 750



HEAVY DUTY GRADE
TENSILIZED, MOPP FILM
EMULSION ACRYLIC ADHESIVE

TENSILE (LBS/IN WIDTH)	145
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	45
THICKNESS (MILS)	5.0
ELONGATION (%)	30
SERVICE TEMPERATURE RANGE (°F)	0 - 250
APPLICABLE STANDARDS*	-

For heavy duty strapping, bundling, banding, palletizing and reinforcing applications.



FILAMENT STRAPPING

GS 490



ECONOMY GRADE
CAST BOPP FILM
SYNTHETIC HOT MELT ADHESIVE
FIBERGLASS REINFORCED

TENSILE (LBS/IN WIDTH)	100
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	70
THICKNESS (MILS)	4.5
ELONGATION (%)	3.7
SERVICE TEMPERATURE RANGE (°F)	-10 - 150
APPLICABLE STANDARDS*	25, 28

For light duty strapping, packaging, bundling and palletizing applications.

GS 500



UTILITY GRADE
CAST BOPP FILM
SYNTHETIC HOT MELT ADHESIVE
FIBERGLASS REINFORCED

TENSILE (LBS/IN WIDTH)	150
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	70
THICKNESS (MILS)	5.2
ELONGATION (%)	3.7
SERVICE TEMPERATURE RANGE (°F)	-10 - 150
APPLICABLE STANDARDS*	25, 28

For general duty strapping, packaging, bundling and palletizing jobs.

GS 501



INDUSTRIAL GRADE
CAST BOPP FILM
SYNTHETIC HOT MELT ADHESIVE
FIBERGLASS REINFORCED

TENSILE (LBS/IN WIDTH)	175
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	70
THICKNESS (MILS)	5.4
ELONGATION (%)	3.7
SERVICE TEMPERATURE RANGE (°F)	-10 - 150
APPLICABLE STANDARDS*	25, 28

For medium duty strapping, packaging, bundling and palletizing applications.

GS 521



HIGH PERFORMANCE GRADE
CAST BOPP FILM
SYNTHETIC HOT MELT ADHESIVE
FIBERGLASS REINFORCED

TENSILE (LBS/IN WIDTH)	300
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	70
THICKNESS (MILS)	6.3
ELONGATION (%)	3.7
SERVICE TEMPERATURE RANGE (°F)	-10 - 150
APPLICABLE STANDARDS*	6, 25, 28

For heavy duty closing, strapping, packaging, bundling, unitizing, palletizing and L-Clip applications.

GS 531



PREMIUM GRADE
POLYESTER FILM (PET)
SYNTHETIC HOT MELT ADHESIVE
FIBERGLASS REINFORCED

TENSILE (LBS/IN WIDTH)	300
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	70
THICKNESS (MILS)	6.7
ELONGATION (%)	3.7
SERVICE TEMPERATURE RANGE (°F)	-10 - 150
APPLICABLE STANDARDS*	6, 25, 28

For heavy duty, maximum security closing, strapping, packaging, protecting, bundling, reinforcing, sealing, unitizing, palletizing and L-Clip applications.

WATER ACTIVATED PAPER

GP 100



**LIGHT DUTY GRADE
NON-REINFORCED KRAFT PAPER
WATER ACTIVATED ADHESIVE**

PAPER SHEET (LBS)	57
MD TENSILE (LBS/IN WIDTH)	45
CD TENSILE (LBS/IN WIDTH)	23
APPLICABLE STANDARDS*	-

For light to medium duty packaging applications such as inner carton sealing or palletized loads.

WP 100



**ECONOMY GRADE
REINFORCED KRAFT PAPER
110 FIBERGLASS
WATER ACTIVATED ADHESIVE**

MD TENSILE (LBS/IN WIDTH)	63
CD TENSILE (LBS/IN WIDTH)	23
TOP SHEET (LBS)	20
BOTTOM SHEET (LBS)	23
MD PATTERN	1-1-1-1
MD SPACING (IN)	9/16
CD SPACING (IN)	1
APPLICABLE STANDARDS*	-

For sealing lightweight cartons up to 20 lbs with minimal exposure to handling, shipping and load stress.

WP 200



**PRODUCTION GRADE
REINFORCED KRAFT PAPER
75/150 FIBERGLASS
WATER ACTIVATED ADHESIVE**

MD TENSILE (LBS/IN WIDTH)	66
CD TENSILE (LBS/IN WIDTH)	27
TOP SHEET (LBS)	20
BOTTOM SHEET (LBS)	25
MD PATTERN	1-1-1-1-1
MD SPACING (IN)	9/16
CD SPACING (IN)	1
APPLICABLE STANDARDS*	-

For sealing medium-weight cartons up to 30 lbs in normal manufacturing and shipping environments; Ideal for single parcel shipments.

WP 300



**PERFORMANCE GRADE
REINFORCED KRAFT PAPER
75/150 FIBERGLASS
WATER ACTIVATED ADHESIVE**

MD TENSILE (LBS/IN WIDTH)	83
CD TENSILE (LBS/IN WIDTH)	30
TOP SHEET (LBS)	25
BOTTOM SHEET (LBS)	25
MD PATTERN	2-1-1-1-2
MD SPACING (IN)	1/2
CD SPACING (IN)	1.5
APPLICABLE STANDARDS*	-

For critical closure of medium-weight cartons up to 55 lbs in all environments, including those subjected to handling stress; Ideal for single parcel shipments.

WP 400



**HEAVY DUTY GRADE
REINFORCED KRAFT PAPER
75/150 FIBERGLASS
WATER ACTIVATED ADHESIVE**

MD TENSILE (LBS/IN WIDTH)	89
CD TENSILE (LBS/IN WIDTH)	32
TOP SHEET (LBS)	25
BOTTOM SHEET (LBS)	30
MD PATTERN	2-2-1-1-2-2
MD SPACING (IN)	1/2
CD SPACING (IN)	17/32
APPLICABLE STANDARDS*	-

For sealing large, bulky or heavy content cartons up to 65 lbs in moderate to severe handling environments; Ideal for single parcel shipments.



MANUAL TAPE APPLICATION – HAND-HELD

SD 932



**STANDARD GRADE
PISTOL-GRIP TAPE DISPENSER
WITH ANTI-REVERSE BAR
2 IN WIDTH MAXIMUM USE**

For manual carton sealing applications.

RECOMMENDED PRODUCTS

AP Series, HP Series, PP Series, FP 96, FP 97, FP 202, VF 719

SD 934



**PROFESSIONAL GRADE
PISTOL-GRIP TAPE DISPENSER
HIGH IMPACT HANDLE, METAL FRAME
2 IN WIDTH MAXIMUM USE**

For manual carton sealing applications.

RECOMMENDED PRODUCTS

AP Series, HP Series, PP Series, FP 96, FP 97, FP 202, VF 719

SD 936



**DELUXE SILENCER
PISTOL-GRIP TAPE DISPENSER
HIGH IMPACT HANDLE, METAL FRAME
2 IN WIDTH MAXIMUM USE**

For manual carton sealing applications.

RECOMMENDED PRODUCTS

AP Series, HP Series, PP Series, FP 96, FP 97, FP 202, VF 719

SD 935



**PROFESSIONAL GRADE
PISTOL-GRIP TAPE DISPENSER
HIGH IMPACT HANDLE, METAL FRAME
3 IN WIDTH MAXIMUM USE**

For manual carton sealing applications.

RECOMMENDED PRODUCTS

AP Series, HP Series, PP Series, FP 96, FP 97, FP 202, VF 719

SD 999



**FILAMENT TAPE DISPENSER
METAL-FRAMED
1 IN WIDTH MAXIMUM USE**

For manual closing, strapping, packaging, bundling and palletizing applications.

RECOMMENDED PRODUCTS

GS Series, PS Series

SD 930



**ECONOMY GRADE
CLAMSHELL TAPE DISPENSER
HIGH IMPACT PLASTIC
2 IN WIDTH MAXIMUM USE**

For manual packaging applications.

RECOMMENDED PRODUCTS

AP Series, HP Series, PP Series, FP 96, FP 97, FP 202, VF 719

MANUAL TAPE APPLICATION – TABLETOP

SD 931



**LABEL PROTECTION DISPENSER
HIGH IMPACT PLASTIC
4 IN WIDTH MAXIMUM USE**

For use on packing lists, sales slips and labels.

RECOMMENDED PRODUCTS

AP 15, PP 807

SD 937



**BAG-SEALING DISPENSER
METAL-FRAMED
9 MM WIDTH MAXIMUM USE**

For single-stroke bag sealing applications.

RECOMMENDED PRODUCTS

PP 808

SD 955



**DESKTOP TAPE DISPENSER
HIGH IMPACT PLASTIC
1 IN WIDTH MAXIMUM USE**

For mending and light duty splicing tasks. Use with tapes with a 1-in or 3-in inside diameter core.

RECOMMENDED PRODUCTS

CT 109

AUTOMATED TAPE APPLICATION

SP 222



**RETROFIT TAPE HEAD
STAINLESS STEEL/ANODIZED ALUMINUM
AVAILABLE IN 2- AND 3-INCH**

For industrial automated carton sealing applications.



ShurSEAL[®] PACKAGING SOLUTIONS

At Shurtape, we've taken a holistic approach to case sealing and developed strategic partnerships to offer packaging tapes and tape application technologies that together deliver better carton seals and packaging line efficiency. The result is ShurSEAL Packaging Solutions, a case sealing system that combines HP Series packaging tape with PrimeLoc™ tape applicators to enhance your case sealing operations.

- Reduce material waste
- Reduce downtime
- Increase safety
- Increase content security
- Reduce maintenance costs



**100%
SATISFACTION
GUARANTEED**

OUR PROMISE TO YOU

If you are not 100% satisfied with the quality or performance of The ShurSEAL Solution, notify us and we'll refund any difference in price compared to your previous supplier.

**FOR MORE DETAILS VISIT
ShurSEALSecure.com**

7000 SERIES



7000 Series Tape Applicators feature

- Easy retrofit into existing erectors and sealers
- Stainless steel wash-down ready construction
- Open design for easy threading
- Front and rear tape tab adjustments
- Good to the Core[®] tape for less material waste
- Consistent seals at speeds up to 200 fpm
- Multiple wipe-down points for the full use of tape's adhesive

8000 SERIES (QUICK CHANGE)



The **8000 Series Quick Change Sealing System** is uniquely engineered to tackle the downtime associated with slow tape roll changeovers, while offering all the benefits of the 7000 Series Applicators.

- Tape roll changes in less than 10 seconds
- Interchangeable inserts allow for easy offline threading
- Lightweight inserts reduce operator strain and lifting
- Retrofits to existing erectors and sealers

FOLDED-EDGE[®] TECHNOLOGY

A patented feature on the tape applicator that folds the edges of the tape as it's applied, reinforcing seal strength and creating a ready to open seal that doesn't require a knife.

- Smoother tape application results in better production throughput
- Increased seal strength at major flaps for added security
- Easy, no-knife opening reduces risk of product damage and worker injury



PRIME ALERT



Tape monitoring system that is self-contained, wireless and self-recharging. Signals line operators if these faults occur: low tape, no tape, broken tape, uncut tape and case jams. Available with optional light tree and PLC integration to shut down conveyors to prevent missed seals from reaching palletizer.

CLOTH & DUCT TAPES

WE KNOW

ALL JOBS HAVE ONE THING IN COMMON: THEY MUST BE DONE RIGHT. THAT'S WHY OUR COMPLETE LINE OF CLOTH AND DUCT TAPES IS ENGINEERED TO EXACTING SPECS. WHEN EASY HANDLING, VARYING ADHESION LEVELS AND DURABLE CONSTRUCTION CHARACTERISTICS ARE NEEDED, TRUST SHURTAPE TO GIVE EVERY JOB A DISTINCTIVE MARK OF

EXCELLENCE.

CO-EXTRUDED DUCT

PC 590



**ECONOMY GRADE
GOOD CONFORMABILITY
NATURAL RUBBER ADHESIVE**

TENSILE (LBS/IN WIDTH)	20
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	54
THICKNESS (MILS)	7.0
ELONGATION (%)	20
SERVICE TEMPERATURE RANGE (°F)	50 - 200
APPLICABLE STANDARDS*	-

For non-critical, general purpose use in packaging, bundling, sealing, seaming, repairing, holding and waterproofing; Also used in the remediation and restoration industries.



PC 595



**GENERAL PURPOSE GRADE
GOOD CONFORMABILITY
NATURAL RUBBER ADHESIVE**

TENSILE (LBS/IN WIDTH)	21
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	55
THICKNESS (MILS)	8.0
ELONGATION (%)	20
SERVICE TEMPERATURE RANGE (°F)	50 - 200
APPLICABLE STANDARDS*	34, 52

For non-critical, general purpose packaging, bundling, sealing, seaming, repairing, holding and waterproofing; Also used in plumbing applications and in the remediation and restoration industries.



When these tapes are combined with other reduced VOC adhesives and sealants used throughout a building, that building is eligible to receive credit toward LEED** certification. In commercial buildings, the credit is one point; in residential construction, the credit is one-half point. That might not seem like a lot, but at Shurtape, we believe it takes everyone doing their part to protect and preserve our environment.

*LEED is a registered trademark owned by the U.S. Green Building Council.

SHURGRIP® CO-EXTRUDED DUCT

PC 460



**SHURGRIP® UTILITY GRADE
GOOD CONFORMABILITY
NATURAL RUBBER ADHESIVE**

TENSILE (LBS/IN WIDTH)	17
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	86
THICKNESS (MILS)	6.0
ELONGATION (%)	20
SERVICE TEMPERATURE RANGE (°F)	40 - 200
APPLICABLE STANDARDS*	-

For non-critical, general purpose use in packaging, bundling, sealing, repairing, holding and waterproofing; Also used in the remediation/abatement industry as a gooseneck tape.



PC 589



**SHURGRIP® LIGHT DUTY
GOOD SHEAR AND ADHESION
NATURAL RUBBER ADHESIVE**

TENSILE (LBS/IN WIDTH)	18
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	106
THICKNESS (MILS)	7.0
ELONGATION (%)	21
SERVICE TEMPERATURE RANGE (°F)	40 - 200
APPLICABLE STANDARDS*	30, 52

For light duty sealing, seaming, repairing, holding and waterproofing applications that require aggressive stick and superior hold; For temporary or permanent use.



PC 600S



**ALL-PURPOSE GRADE
CONFORMABLE
NATURAL RUBBER ADHESIVE**

TENSILE (LBS/IN WIDTH)	22
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	50
THICKNESS (MILS)	9.0
ELONGATION (%)	16
SERVICE TEMPERATURE RANGE (°F)	50 - 200
APPLICABLE STANDARDS*	5

For general purpose use in industrial, carpet, plumbing, HVAC, sealing, waterproofing, patching, remediation and restoration applications.



PC 618S



**PERFORMANCE GRADE
EXCELLENT CONFORMABILITY
NATURAL RUBBER ADHESIVE**

TENSILE (LBS/IN WIDTH)	27
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	55
THICKNESS (MILS)	10.0
ELONGATION (%)	17
SERVICE TEMPERATURE RANGE (°F)	50 - 200
APPLICABLE STANDARDS*	38, 52

For holding, securing, seaming, repairing, bundling, splicing, packaging and masking in HVAC, industrial, commercial, utilities, trucking and automotive applications; Can also be used as a condensation barrier in appliance assemblies.



For ultimate performance, choose Shurtape duct tapes with Polybonded CO-EX Technology®. The co-extrusion process melds polyethylene, cloth and adhesive in a single, high-temperature step, resulting in a permanent, airtight bond. This seamless construction creates added strength and will not delaminate.

PC 593



**SHURGRIP® MEDIUM DUTY
GOOD SHEAR AND ADHESION
NATURAL RUBBER ADHESIVE**

TENSILE (LBS/IN WIDTH)	19
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	127
THICKNESS (MILS)	8.0
ELONGATION (%)	21
SERVICE TEMPERATURE RANGE (°F)	40 - 200
APPLICABLE STANDARDS*	30, 52

For medium duty sealing, seaming, repairing, holding and waterproofing applications that require aggressive stick and superior hold; Also used in the restoration industry; For temporary or permanent use.



PC 599



**SHURGRIP® HEAVY DUTY
EXCELLENT SHEAR AND ADHESION
NATURAL RUBBER ADHESIVE**

TENSILE (LBS/IN WIDTH)	20
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	131
THICKNESS (MILS)	9.0
ELONGATION (%)	21
SERVICE TEMPERATURE RANGE (°F)	40 - 200
APPLICABLE STANDARDS*	30, 52

For heavy duty sealing, seaming, repairing, holding and waterproofing applications that require aggressive stick and superior hold; Also used in the restoration industry; For temporary or permanent use.



COLORED & PRINTED DUCT

PC 600C



**ALL-PURPOSE GRADE
CONFORMABLE
NATURAL RUBBER ADHESIVE**

TENSILE (LBS/IN WIDTH)	22
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	50
THICKNESS (MILS)	9.0
ELONGATION (%)	16
SERVICE TEMPERATURE RANGE (°F)	50 - 200
APPLICABLE STANDARDS*	5

For general purpose use in industrial, plumbing, carpet, color-coding and splicing applications, as well as home and general repair applications, particularly where a discreet fix is needed.



PC 618C



**PERFORMANCE GRADE
EXCELLENT CONFORMABILITY
NATURAL RUBBER ADHESIVE**

TENSILE (LBS/IN WIDTH)	27
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	55
THICKNESS (MILS)	10.0
ELONGATION (%)	17
SERVICE TEMPERATURE RANGE (°F)	50 - 200
APPLICABLE STANDARDS*	38, 52

For holding, securing, seaming, repairing, bundling, splicing, packaging and masking in HVAC, industrial, commercial, utilities, trucking and automotive applications; Can also be used as a condensation barrier in appliance assemblies.



PC 619



**SPECIALTY GRADE
CONFORMABLE
NATURAL RUBBER ADHESIVE**

TENSILE (LBS/IN WIDTH)	22
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	50
THICKNESS (MILS)	9.0
ELONGATION (%)	16
SERVICE TEMPERATURE RANGE (°F)	50 - 200
APPLICABLE STANDARDS*	5

For general use, including color-coding, labeling, floor marking and book-binding; Also used for stage preparation in the motion picture and audio/visual industries; Can also be used for a variety of applications in the hospitality, motorsports and floral industries.



PC 626



**SPECIALTY GRADE
LUSTERLESS CAMOUFLAGE
OFFICIAL ARMY ACU DIGITAL
NATURAL RUBBER ADHESIVE**

TENSILE (LBS/IN WIDTH)	23
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	48
THICKNESS (MILS)	10.0
ELONGATION (%)	20
SERVICE TEMPERATURE RANGE (°F)	50 - 200
APPLICABLE STANDARDS*	5

For sealing, waterproofing, holding, camouflaging, sound deadening, covering reflective surfaces and patching applications.



PERFORMANCE DUCT

PC 609



**PERFORMANCE GRADE
EXCELLENT HOLD
BLENDED RUBBER ADHESIVE**

TENSILE (LBS/IN WIDTH)	22
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	71
THICKNESS (MILS)	10.0
ELONGATION (%)	16
SERVICE TEMPERATURE RANGE (°F)	25 - 200
APPLICABLE STANDARDS*	30, 52

For use in the HVAC industry to repair thermal insulation and flexible ducts, and to seal metal ductwork; Used in the manufactured housing industry to seam bottom boards and for patching, seaming and sealing; Used for packaging, bundling, holding, wrapping and waterproofing; Also used for asbestos and mold remediation.



PC 610



**PERFORMANCE GRADE ABATEMENT
SUPERIOR HOLD
BLENDED RUBBER ADHESIVE**

TENSILE (LBS/IN WIDTH)	21
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	56
THICKNESS (MILS)	10.0
ELONGATION (%)	18
SERVICE TEMPERATURE RANGE (°F)	25 - 200
APPLICABLE STANDARDS*	-

For sealing walls, doors and windows in abatement applications; Ideal for use on rugged jobs in warm and cold climates, as well as dry and wet environments.

PC 629



**INDUSTRIAL GRADE ABATEMENT
SUPERIOR HOLD
BLENDED RUBBER ADHESIVE**

TENSILE (LBS/IN WIDTH)	27
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	58
THICKNESS (MILS)	11.0
ELONGATION (%)	20
SERVICE TEMPERATURE RANGE (°F)	25 - 200
APPLICABLE STANDARDS*	-

For sealing walls, doors and windows in abatement applications; Ideal for use on rugged jobs in warm and cold climates, as well as dry and wet environments.

SF 682



**SHURFLEX® PROFESSIONAL GRADE
FLEXIBLE AND CONFORMABLE
NATURAL RUBBER ADHESIVE**

TENSILE (LBS/IN WIDTH)	25
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	55
THICKNESS (MILS)	10.0
ELONGATION (%)	18
SERVICE TEMPERATURE RANGE (°F)	50 - 200
APPLICABLE STANDARDS*	31, 52

For use in the HVAC industry for airtight and moisture-free seaming, connecting, splicing, patching and sealing of sheet metal and flex duct, rigid duct boards, air vents, insulation, fibrous filter banks and pollution collection systems.



SF 683



**SHURFLEX® PROFESSIONAL GRADE
FLEXIBLE AND CONFORMABLE
NATURAL RUBBER ADHESIVE**

TENSILE (LBS/IN WIDTH)	25
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	55
THICKNESS (MILS)	10.0
ELONGATION (%)	18
SERVICE TEMPERATURE RANGE (°F)	50 - 200
APPLICABLE STANDARDS*	31, 52

For use in the HVAC industry for airtight and moisture-free seaming, connecting, splicing, patching and sealing of sheet metal and flex duct, insulation, rigid duct boards, air vents and fiber board.



HEAVY DUTY DUCT

PC 621



**PROFESSIONAL GRADE
EXCELLENT CONFORMABILITY
NATURAL RUBBER ADHESIVE**

TENSILE (LBS/IN WIDTH)	27
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	62
THICKNESS (MILS)	11.0
ELONGATION (%)	10
SERVICE TEMPERATURE RANGE (°F)	50 - 200
APPLICABLE STANDARDS*	34, 52

For demanding HVAC applications to hold, seal and seam sheet metal and flex duct, exhaust vents and preformed insulation; Can also be used in industrial applications for holding, splicing, protecting and packaging.



PC 721



**EXTREME HOLD PROFESSIONAL GRADE
EXCELLENT CONFORMABILITY
NATURAL RUBBER ADHESIVE**

TENSILE (LBS/IN WIDTH)	32
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	60
THICKNESS (MILS)	11.5
ELONGATION (%)	24
SERVICE TEMPERATURE RANGE (°F)	50 - 200
APPLICABLE STANDARDS*	34, 52

For demanding HVAC applications to hold, seal and seam sheet metal; Can also be used for heavy duty industrial applications like holding, bundling, splicing, protecting and packaging.



SUPER PERFORMANCE DUCT

PC 658



**SUPER BOTTOM BOARD
SUPERIOR ADHESION AND HOLD
NATURAL RUBBER ADHESIVE**

TENSILE (LBS/IN WIDTH)	30
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	125
THICKNESS (MILS)	17.0
ELONGATION (%)	10
SERVICE TEMPERATURE RANGE (°F)	50 - 200
APPLICABLE STANDARDS*	37, 52

For seaming and sealing bottom board materials in pre-manufactured housing and RV assembly, set-up and maintenance; Can also be used to protect surfaces in metal-peening operations.



SPECIALTY PERFORMANCE DUCT

PC 623



**ECONOMICAL NUCLEAR GRADE
EXCELLENT HOLDING POWER
NATURAL RUBBER ADHESIVE
MEETS ASME NQA-1 GUIDELINES**

TENSILE (LBS/IN WIDTH)	28
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	58
THICKNESS (MILS)	11.5
ELONGATION (%)	12
SERVICE TEMPERATURE RANGE (°F)	50 - 200
APPLICABLE STANDARDS*	2, 3, 46

For a variety of purposes in the construction, operation and maintenance of nuclear power facilities; Can also be used for holding to stainless steel pipes, color-coding and sealing endcaps on stainless steel pipes.



PC 624



**NUCLEAR GRADE
EXCELLENT HOLDING POWER
NATURAL RUBBER ADHESIVE
MEETS ASME NQA-1 GUIDELINES**

TENSILE (LBS/IN WIDTH)	36
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	60
THICKNESS (MILS)	13.0
ELONGATION (%)	14
SERVICE TEMPERATURE RANGE (°F)	50 - 200
APPLICABLE STANDARDS*	2, 3, 46

For a more robust variety of purposes in the construction, operation and maintenance of nuclear power facilities; Can also be used for holding to stainless steel pipes, color-coding and sealing endcaps on stainless steel pipes.



PC 625



**MILITARY SPEC LUSTERLESS
EXCELLENT HOLDING POWER
NATURAL RUBBER ADHESIVE
ASTM D5486M TESTED**

TENSILE (LBS/IN WIDTH)	45
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	50
THICKNESS (MILS)	12.5
ELONGATION (%)	12
SERVICE TEMPERATURE RANGE (°F)	50 - 200
APPLICABLE STANDARDS*	10

For use as a premium, waterproof packaging tape that meets government specifications; Can also be used for moisture-proofing cartons, canisters and tubing.



PC 657®



**HEAVY DUTY PROFESSIONAL GRADE
EXCELLENT HOLD
NATURAL RUBBER ADHESIVE**

TENSILE (LBS/IN WIDTH)	29
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	104
THICKNESS (MILS)	14.5
ELONGATION (%)	11
SERVICE TEMPERATURE RANGE (°F)	50 - 200
APPLICABLE STANDARDS*	40, 52

For use in high performance motorsports applications, pre-manufactured housing and RV assembly, critical industrial applications and for protection during metal-peening operations.



T-REX®



**SUPER-TOUGH, ALL-WEATHER
QUICK STICK
NATURAL RUBBER ADHESIVE**

TENSILE (LBS/IN WIDTH)	52
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	90
THICKNESS (MILS)	17.0
ELONGATION (%)	10
SERVICE TEMPERATURE RANGE (°F)	50 - 200
APPLICABLE STANDARDS*	-

For use on rough or dirty surfaces; For heavy duty repairs that demand a ferociously strong hold; Can also be used as a bottom board tape in the manufactured housing industry.



COATED CLOTH

P- 628



PROFESSIONAL GRADE GAFFER'S MATTE-FINISH BACKING
HIGH TENSILE AND HOLDING POWER
SYNTHETIC RUBBER ADHESIVE

TENSILE (LBS/IN WIDTH)	50
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	75
THICKNESS (MILS)	10.75
ELONGATION (%)	4
SERVICE TEMPERATURE RANGE (°F)	50 - 200
APPLICABLE STANDARDS*	-

For use in the convention, hospitality, exhibition and trade show industries, and for general use in the audio/visual, television, photography, theatrical and motion picture industries; Used for protection and book-binding, color-coding, labeling and stage marking; Also used in the HVAC industry.



P- 661



GLOW-IN-THE-DARK GAFFER'S WRITABLE/PRINTABLE
HIGH ADHESION AND TACK
SYNTHETIC RUBBER ADHESIVE

TENSILE (LBS/IN WIDTH)	50
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	80
THICKNESS (MILS)	13.0
ELONGATION (%)	4
SERVICE TEMPERATURE RANGE (°F)	50 - 200
APPLICABLE STANDARDS*	5, 14

Used for a multitude of applications, including safety marking, in the audio/visual, television, photography, theatrical and motion picture industries; Also used for labeling and marking various objects, such as: safety/critical equipment, exit/directional signage, tripping hazards, access handles, sports equipment and tools.



P- 660



PROFESSIONAL GRADE GAFFER'S MATTE-FINISH BACKING
HIGH TENSILE AND HOLDING POWER
SYNTHETIC RUBBER ADHESIVE

TENSILE (LBS/IN WIDTH)	50
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	75
THICKNESS (MILS)	10.75
ELONGATION (%)	4
SERVICE TEMPERATURE RANGE (°F)	50 - 200
APPLICABLE STANDARDS*	-

For bundling or securing wires, cables and props in the audio/visual, television, photography, theatrical and motion picture industries; Also used for color-coding, labeling, marking and book-binding applications. Will fluoresce under black light.

P- 665®



PROFESSIONAL GRADE GAFFER'S MATTE-FINISH BACKING
HIGH ADHESION AND TACK
SYNTHETIC RUBBER ADHESIVE

TENSILE (LBS/IN WIDTH)	50
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	80
THICKNESS (MILS)	11.0
ELONGATION (%)	4
SERVICE TEMPERATURE RANGE (°F)	50 - 200
APPLICABLE STANDARDS*	17

For demanding applications that require clean removal in the audio/visual, television, photography, theatrical and motion picture industries, such as holding wiring, lighting and props.

P- 672®



PREMIUM GRADE GAFFER'S LIGHT DUTY
MATTE-FINISH BACKING
SYNTHETIC RUBBER ADHESIVE

TENSILE (LBS/IN WIDTH)	70
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	77
THICKNESS (MILS)	12.0
ELONGATION (%)	6
SERVICE TEMPERATURE RANGE (°F)	50 - 200
APPLICABLE STANDARDS*	17

For sealing containers and protection from welding splatter; Can also be used for general holding, bundling and temporary repair applications.

P- 691®



PREMIUM GRADE GAFFER'S MEDIUM DUTY
MATTE-FINISH BACKING
SYNTHETIC RUBBER ADHESIVE

TENSILE (LBS/IN WIDTH)	70
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	80
THICKNESS (MILS)	12.25
ELONGATION (%)	6
SERVICE TEMPERATURE RANGE (°F)	50 - 200
APPLICABLE STANDARDS*	17, 44

For sealing containers and rooms, abrasion protection, and general holding, bundling and repair applications; Meets water leachable requirements for detrimental elements (Fl & Br <250PPM; S & C<500PPM) in accordance with MIL-STD-2041D.

P- 68



PREMIUM GRADE GAFFER'S HEAVY DUTY
MATTE-FINISH BACKING
SYNTHETIC RUBBER ADHESIVE

TENSILE (LBS/IN WIDTH)	70
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	83
THICKNESS (MILS)	12.5
ELONGATION (%)	6
SERVICE TEMPERATURE RANGE (°F)	50 - 200
APPLICABLE STANDARDS*	17

For book-binding, color-coding and gaffer's applications; For sealing containers and rooms, abrasion protection, and general holding, bundling and repair applications.

P- 670



HEAVY DUTY DUCT TAPE
POLYETHYLENE COATED BACKING
SYNTHETIC RUBBER ADHESIVE

TENSILE (LBS/IN WIDTH)	30
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	95
THICKNESS (MILS)	11.5
ELONGATION (%)	3
SERVICE TEMPERATURE RANGE (°F)	50 - 200
APPLICABLE STANDARDS*	-

For sealing and seaming ductwork in the HVAC industry; Can also be used for protection, splicing, bundling, seaming and sealing applications that demand higher tensile strength and easy tear capabilities; For temporary and permanent uses in the auto industry.



STUCCO MASKING

PC 567



SPECIALTY GRADE, CLOTH DUCT CONFORMABLE TO MOST SURFACES BLENDED RUBBER ADHESIVE

TENSILE (LBS/IN WIDTH)	21
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	46
THICKNESS (MILS)	8.0
ELONGATION (%)	14
SERVICE TEMPERATURE RANGE (°F)	50 - 200
APPLICABLE STANDARDS*	30, 52

For protecting surfaces when pressure washing and applying stucco.



PC 667



SPECIALTY GRADE, CLOTH DUCT EASY TO TEAR BLENDED RUBBER ADHESIVE

TENSILE (LBS/IN WIDTH)	22
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	50
THICKNESS (MILS)	9.0
ELONGATION (%)	15
SERVICE TEMPERATURE RANGE (°F)	50 - 200
APPLICABLE STANDARDS*	-

For protective masking of non-painted surfaces, including steel, vinyl, aluminum and anodized metals; Use in plastering, stucco, concrete, pool and tile applications.



PC 668



SPECIALTY GRADE, CLOTH DUCT HOLDS STRONG SYNTHETIC/NATURAL RUBBER ADHESIVE

TENSILE (LBS/IN WIDTH)	27.5
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	70
THICKNESS (MILS)	11.0
ELONGATION (%)	15
SERVICE TEMPERATURE RANGE (°F)	50 - 200
APPLICABLE STANDARDS*	-

For two- and three-step (scratch, brown and finish) stucco processes where the job requirements dictate the protective barrier be left in place for the entire application.



PC 622



PREMIUM GRADE CLOTH DUCT CONFORMABLE WITH EXCELLENT HOLD NATURAL RUBBER ADHESIVE

TENSILE (LBS/IN WIDTH)	36
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	60
THICKNESS (MILS)	12.5
ELONGATION (%)	14
SERVICE TEMPERATURE RANGE (°F)	50 - 200
APPLICABLE STANDARDS*	36, 52

For protecting window and door frames during stucco applications; Used in high performance motorsports; For heavy duty bundling, holding and splicing.



PE 333



POLYETHYLENE FILM SERRATED OR STRAIGHT EDGE MAINTAINS A WATERTIGHT SEAL SYNTHETIC RUBBER ADHESIVE

TENSILE (LBS/IN WIDTH)	19
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	70
THICKNESS (MILS)	7.0
ELONGATION (%)	80
SERVICE TEMPERATURE RANGE (°F)	32 - 160
APPLICABLE STANDARDS*	-

For masking surfaces, such as windows and doors, during stucco application and painting when UV resistance is not required; Also for seaming under slab vapor barriers; Delivers residue-free removal for a variety of applications.

PE 444



POLYETHYLENE FILM MAINTAINS A WATERTIGHT SEAL SYNTHETIC RUBBER ADHESIVE

TENSILE (LBS/IN WIDTH)	19
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	80
THICKNESS (MILS)	7.0
ELONGATION (%)	76
SERVICE TEMPERATURE RANGE (°F)	32 - 160
APPLICABLE STANDARDS*	-

For masking surfaces, such as windows and doors, during stucco application and painting; Delivers residue-free removal for a variety of applications.



PE 555



POLYETHYLENE FILM EXCELLENT TEARABILITY SYNTHETIC RUBBER ADHESIVE

TENSILE (LBS/IN WIDTH)	27
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	92
THICKNESS (MILS)	9.0
ELONGATION (%)	94
SERVICE TEMPERATURE RANGE (°F)	32 - 160
APPLICABLE STANDARDS*	-

For masking surfaces during stucco application and painting; Can also be used for surface protection, color-coding, splicing and seaming on pipe-fitting covers; Delivers residue-free removal for a variety of applications.



A close-up photograph of a person's hands applying a roll of silver foil tape to a corrugated metal duct. The duct is lying on its side, and the person is using their hands to peel the tape from its roll and press it onto the metal surface. In the foreground, another roll of the same tape lies on the floor. The background is slightly blurred, showing a workshop or construction site environment.

FOIL & FILM TAPES

WE KNOW YOUR REPUTATION IS ON THE LINE. THAT'S WHY WE OFFER A COMPREHENSIVE LINE OF FOIL, FILM AND COMPOSITE HVAC TAPES THAT ARE ENGINEERED TO DELIVER FULL SYSTEM CLOSURE. WITH OPTIONS TO MEET THE CODE, PERFORM IN THE COLD AND HELP YOU QUALIFY FOR LEED® CREDITS, SHURTAPE HAS YOU COVERED WITH THE TAPES YOU NEED TO ENSURE EVERYTHING IS PROPERLY SEALED TO YOUR **EXACTING STANDARDS.**

UL 181B-FX LISTED

PC 857



**UL PRINTED COATED CLOTH
HIGH STRENGTH AND HOLD
SYNTHETIC RUBBER BLEND ADHESIVE**

TENSILE (LBS/IN WIDTH)	27
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	70
THICKNESS (MILS)	14.0
ELONGATION (%)	10
SERVICE TEMPERATURE RANGE (°F)	50 - 212
APPLICABLE STANDARDS*	39, 51, 52, 53

Used in the HVAC industry to seal, seam and join Class 1 Flex Duct.



PC 858CA



**UL PRINTED COATED CLOTH
HIGH STRENGTH AND HOLD
SYNTHETIC RUBBER BLEND ADHESIVE
CEC APPROVED**

TENSILE (LBS/IN WIDTH)	27
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	70
THICKNESS (MILS)	14.0
ELONGATION (%)	10
SERVICE TEMPERATURE RANGE (°F)	50 - 212
APPLICABLE STANDARDS*	39, 51, 52, 53

Used in the HVAC industry to seal, seam and join Class 1 Flex Duct; Approved for use by the California Energy Commission.



ROLL MASTIC

SF 685



**PRINTED SHURMASTIC® FOIL
FORMS A PERMANENT BOND
BUTYL RUBBER ADHESIVE
LINERED**

TENSILE (LBS/IN WIDTH)	25
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	255
THICKNESS (MILS)	17.0
ELONGATION (%)	560
SERVICE TEMPERATURE RANGE (°F)	-20 - 200
APPLICABLE STANDARDS*	41, 47, 49, 52

For indoor or outdoor use to seal Class 1 Flex Duct, sheet metal and duct wrap vapor barriers; Also approved for subgrade application on PVC-coated duct; Paintable with paint recommended for aluminum.



COLD TEMPERATURE FOILS

AF 914CT



**1.5-MIL ALUMINUM FOIL
SUPERIOR STABILITY
ACRYLIC-BASED ADHESIVE
LINERED**

TENSILE (LBS/IN WIDTH)	12
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	64
THICKNESS WITHOUT LINER (MILS)	3.4
ELONGATION (%)	3
APPLICATION TEMPERATURE RANGE (°F)	-20 - 260
APPLICABLE STANDARDS*	30, 52

For joining and sealing aluminum-backed and fibrous insulation and metal ductwork in temperatures ranging from -20 F to 260 F; Also used to repair metal and sheet metal.



AF 975CT



**2-MIL ALUMINUM FOIL
SUPERIOR STABILITY
ACRYLIC-BASED ADHESIVE
LINERED**

TENSILE (LBS/IN WIDTH)	18
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	64
THICKNESS WITHOUT LINER (MILS)	4.0
ELONGATION (%)	3
APPLICATION TEMPERATURE RANGE (°F)	-20 - 260
APPLICABLE STANDARDS*	30, 52

For use in temperatures ranging from -20 F to 260 F when joining and sealing aluminum-backed or fibrous insulation and metal ductwork; Can also be used when repairing metal and sheet metal.



DC 181



**UL PRINTED BOPP FILM
EXCELLENT CONFORMABILITY
ACRYLIC ADHESIVE**

TENSILE (LBS/IN WIDTH)	31
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	38
THICKNESS (MILS)	2.7
ELONGATION (%)	200
SERVICE TEMPERATURE RANGE (°F)	-10 - 210
APPLICABLE STANDARDS*	42, 51, 52, 53

For use on Class 1 Flex Duct for connecting, joining, sealing and patching flexible air ductwork.



SF 686



**UL PRINTED SHURMASTIC® FOIL
INSTANT, WATER-RESISTANT GRIP
BUTYL RUBBER ADHESIVE
LINERED**

TENSILE (LBS/IN WIDTH)	23.8
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	111
THICKNESS (MILS)	17.0
ELONGATION (%)	-
SERVICE TEMPERATURE RANGE (°F)	-20 - 220
APPLICABLE STANDARDS*	47, 49, 51, 52, 53

For airtight and moisture-free sealing of Class 1 Flex Duct, sheet metal and duct wrap vapor barriers; Also approved for subgrade application on PVC-coated duct; Paintable with paint recommended for aluminum.



AF 984CT



**FOIL/SCRIM/KRAFT (FSK)
SUPERIOR STABILITY
ACRYLIC-BASED ADHESIVE
LINERED**

TENSILE (LBS/IN WIDTH)	34
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	64
THICKNESS WITHOUT LINER (MILS)	7.4
ELONGATION (%)	3
APPLICATION TEMPERATURE RANGE (°F)	-20 - 260
APPLICABLE STANDARDS*	33, 52

For sealing seams in scrim-reinforced duct insulation.



AF 990CT



**ALL SERVICE JACKET (ASJ)
SUPERIOR STABILITY
ACRYLIC-BASED ADHESIVE
LINERED**

TENSILE (LBS/IN WIDTH)	50
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	80
THICKNESS WITHOUT LINER (MILS)	8.3
ELONGATION (%)	6.7
APPLICATION TEMPERATURE RANGE (°F)	-20 - 260
APPLICABLE STANDARDS*	35, 52

For use in cold and dual temperature systems to seal, seam and join scrim-reinforced pipe and duct insulation.



UL 181A-P/B-FX LISTED

AF 100



**2-MIL DEAD-SOFT ALUMINUM FOIL
FLEXIBLE AND EASY TO USE
ACRYLIC-BASED ADHESIVE
TRADITIONAL OR EASYPEEL™ LINER**

TENSILE (LBS/IN WIDTH)	25
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	70
THICKNESS WITHOUT LINER (MILS)	4.2
ELONGATION (%)	2
APPLICATION TEMPERATURE RANGE (°F)	-20 - 260
APPLICABLE STANDARDS*	42, 50, 51, 52, 53

For airtight joining and sealing joints, connections and seams on rigid fiberglass duct board and flexible air duct.



ALUMINUM & PAPER COMPOSITE

AF 75



**3-MIL DEAD-SOFT ALUMINUM FOIL
EXCELLENT ADHESION TO BACKING
ACRYLIC-BASED ADHESIVE
LINERLESS**

TENSILE (LBS/IN WIDTH)	30
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	55
THICKNESS (MILS)	4.8
ELONGATION (%)	5.3
APPLICATION TEMPERATURE RANGE (°F)	-10 - 180
APPLICABLE STANDARDS*	43, 45, 46, 48

For use in broad temperature ranges to create vapor barriers and waterproof seals; Also used for masking off surfaces when painting and electroplating.

AF 912



**1.5-MIL DEAD-SOFT ALUMINUM FOIL
SOLVENT-FREE
SYNTHETIC RUBBER ADHESIVE
LINERED**

TENSILE (LBS/IN WIDTH)	11
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	90
THICKNESS WITHOUT LINER (MILS)	3.8
ELONGATION (%)	2
APPLICATION TEMPERATURE RANGE (°F)	32 - 230
APPLICABLE STANDARDS*	34, 52

For sealing and joining aluminum-backed duct wrap; Also used for temporary metal repair.



SPECIALTY TAPES

HW 300



**HOUSEWRAP/SHEATHING
HAND-TEARABLE
WATER-BASED ACRYLIC ADHESIVE
CCMC-CERTIFIED**

TENSILE (LBS/IN WIDTH)	30
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	50
THICKNESS (MILS)	3.0
ELONGATION (%)	162
APPLICATION TEMPERATURE RANGE (°F)	14 - 176
APPLICABLE STANDARDS*	15, 30, 52

For sealing seams and joints on all types of housewrap, sheathing, insulation and vapor barrier materials used in residential and commercial construction applications.



IT 100



**GENERAL PURPOSE GRADE
FOAM PIPE WRAP INSULATION
ADHERES FIRMLY TO ALL METALS
ACRYLIC-BASED ADHESIVE**

TENSILE (LBS/IN WIDTH) (LONGITUDINAL)	6.0
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	-
THICKNESS WITHOUT LINER (MILS)	118.1
ELONGATION (%) (MACHINE DIRECTION)	126
SERVICE TEMPERATURE RANGE (°F)	-20 - 180
APPLICABLE STANDARDS*	-

For hot and cold pipe insulation applications - cover hot pipes to prevent heat loss and cold pipes to prevent condensation drip; Thermal conductivity is 0.28 at 75 F, in accordance with ASTM C-177.

PVC FILM

BT 100



**GENERAL PURPOSE BARRICADE
2-IN LETTERS ARE EASY TO READ
RESISTS SAGGING
ADHESIVE-FREE**

THICKNESS (MILS)	2 - 3
APPLICABLE STANDARDS*	-

For marking restricted areas and managing access to work sites by professionals in the safety, construction, utilities, hardware and other industries.

EV 57B



**GENERAL PURPOSE GRADE
UL LISTED ELECTRICAL
HIGH TENSILE AND ELONGATION
MATTE-FINISH SPVC FILM**

TENSILE (LBS/IN WIDTH)	14
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	16
THICKNESS (MILS)	7.0
ELONGATION (%)	200
SERVICE TEMPERATURE RANGE (°F)	20 - 176
APPLICABLE STANDARDS*	23, 53

For splicing, insulating and binding wiring harnesses; Dielectric at break 1,000 volts/mil.



AF 973



**2-MIL DEAD-SOFT ALUMINUM FOIL
SOLVENT-FREE
SYNTHETIC RUBBER ADHESIVE
LINERED**

TENSILE (LBS/IN WIDTH)	15
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	90
THICKNESS WITHOUT LINER (MILS)	4.4
ELONGATION (%)	2
APPLICATION TEMPERATURE RANGE (°F)	32 - 230
APPLICABLE STANDARDS*	32, 52

For sealing and joining aluminum-backed duct wrap, creating water and vapor barriers, and for temporary metal repair.



AF 982



**FOIL/SCRIM/KRAFT (FSK)
SOLVENT-FREE
SYNTHETIC RUBBER ADHESIVE
LINERED**

TENSILE (LBS/IN WIDTH)	40
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	60
THICKNESS WITHOUT LINER (MILS)	6.6
ELONGATION (%)	1
APPLICATION TEMPERATURE RANGE (°F)	32 - 230
APPLICABLE STANDARDS*	36, 52

For maximum-strength sealing, seaming and joining scrim-reinforced pipe and duct insulation in all weather conditions.



LS 300



**UV-RESISTANT LINE SET
EASY TO UNWIND
ACRYLIC-BASED ADHESIVE**

TENSILE (LBS/IN WIDTH)	37
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	35
THICKNESS (MILS)	2.85
ELONGATION (%)	180
SERVICE TEMPERATURE RANGE (°F)	-35 - 210
APPLICABLE STANDARDS*	-

For taping outdoor HVAC components.



PW 100



**GENERAL PURPOSE GRADE
PVC PIPE WRAP
CORROSION/MOISTURE RESISTANT
RUBBER-BASED ADHESIVE**

TENSILE (LBS/IN WIDTH)	32
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	20
THICKNESS (MILS)	10.0
ELONGATION (%)	200
APPLICATION TEMPERATURE RANGE (°F)	14 - 176
SERVICE TEMPERATURE RANGE (°F)	32 - 104
APPLICABLE STANDARDS*	-

For corrosion protection of underground metal and plastic pipe installations.

VP 410



**GENERAL PURPOSE GRADE
LINE SET
SPVC FILM**

TENSILE (LBS/IN WIDTH)	13
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	20
THICKNESS (MILS)	5.25
ELONGATION (%)	200
SERVICE TEMPERATURE RANGE (°F)	20 - 140
APPLICABLE STANDARDS*	19

For floor, lane and aisle marking, color-coding and identification applications; Also used in the HVAC industry to wrap line sets, seam Rubatex and Armaflex, and insulate air ducts and underground pipes; Meets OSHA color-coding requirements.



VP 415



**GENERAL PURPOSE GRADE
WARNING STRIPE
SPVC FILM**

TENSILE (LBS/IN WIDTH)	15
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	12
THICKNESS (MILS)	6.6
ELONGATION (%)	200
SERVICE TEMPERATURE RANGE (°F)	20 - 140
APPLICABLE STANDARDS*	19

For lane marking and identification of safety zones and hazard areas; Resistant to abrasion, UV light, acid, alkalides, oils, moisture, humidity and corrosion; Meets OSHA color-coding requirements.



DOUBLE-COATED TAPES

WE KNOW YOU DEMAND VERSATILITY TO GET THE JOB DONE. THAT'S WHY WE HAVE ENGINEERED A COMPREHENSIVE ASSORTMENT OF DOUBLE-COATED TAPES, INCLUDING PAPER, FILM, CLOTH AND TRANSFER ADHESIVE OPTIONS. WHETHER YOU'RE MOUNTING, SPLICING, JOINING OR LAMINATING, THESE TAPES HAVE ONE THING IN COMMON: AN UNSURPASSED LEVEL OF **QUALITY.**

DOUBLE-COATED PAPER

DF 63



**GENERAL PURPOSE GRADE
CREPE PAPER
RUBBER-BASED ADHESIVE**

TENSILE (LBS/IN WIDTH)	23
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	35
THICKNESS WITHOUT LINER (MILS)	6.5
ELONGATION (%)	9
SERVICE TEMPERATURE RANGE (°F)	50 - 225
APPLICABLE STANDARDS*	21

For mounting, holding, splicing, tabbing and fastening a variety of substrates.

DF 65



**GENERAL PURPOSE GRADE
FLAT PAPER
RUBBER-BASED ADHESIVE**

TENSILE (LBS/IN WIDTH)	33
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	66
THICKNESS WITHOUT LINER (MILS)	5.0
ELONGATION (%)	2.5
SERVICE TEMPERATURE RANGE (°F)	50 - 225
APPLICABLE STANDARDS*	22

For mounting, holding, splicing, tabbing and fastening applications that demand aggressive adhesion.

DT 200



**PREMIUM PERFORMANCE GRADE
SOLVENT-BASED ACRYLIC ADHESIVE
NONWOVEN TISSUE**

TENSILE (LBS/IN WIDTH)	5
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	55
THICKNESS WITHOUT LINER (MILS)	4.5
ELONGATION (%)	3.5
SERVICE TEMPERATURE RANGE (°F)	-20 - 212
APPLICABLE STANDARDS*	-

For high-speed splicing in the corrugated cardboard production process in temperatures up to 400 F; Can also be used as a mounting and laminating system for irregularly shaped metals, foams, foils and nameplates; For manual applications.

DOUBLE-COATED FILM

DP 401



**PROFESSIONAL GRADE
POLYESTER (PET) FILM
SYNTHETIC RUBBER ADHESIVE**

TENSILE (LBS/IN WIDTH)	14
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH) (LS^)	124
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH) (ES^)	142
THICKNESS WITHOUT LINER (MILS)	4.7
ELONGATION (%)	100
SERVICE TEMPERATURE RANGE (°F)	32 - 150
APPLICABLE STANDARDS*	-

For polyethylene (PE) foam fabrication and lamination processes. Ideal for packaging applications that require cushioning, protection or stabilization of contents; Can also be used with die-cuts, gaskets, POP merchandising and shelf displays.

^LS=LINER SIDE; ^ES=EXPOSED SIDE



DOUBLE-COATED CLOTH

DF 545



**PREMIUM PERFORMANCE GRADE
POLYESTER/COTTON BLEND CLOTH
RUBBER-BASED ADHESIVE**

TENSILE (LBS/IN WIDTH)	28
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	45
THICKNESS WITHOUT LINER (MILS)	13.5
ELONGATION (%)	9
SERVICE TEMPERATURE RANGE (°F)	50 - 200
APPLICABLE STANDARDS*	-

For securing carpet and pad at convention centers, arenas and hotels; Also used for general purpose hanging applications in the construction and abatement industries; Can also be used for splicing applications.

DS 154



**PROFESSIONAL GRADE CONTAINMENT
EXCELLENT HOLD
FINE STRUCTURED CREPE (FSC)
SYNTHETIC RUBBER ADHESIVE**

TENSILE (LBS/IN WIDTH)	21
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH) (LS^)	60
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH) (ES^)	27
THICKNESS WITHOUT LINER (MILS)	8.5
ELONGATION (%)	9
SERVICE TEMPERATURE RANGE (°F)	32 - 120
APPLICABLE STANDARDS*	-

For holding poly-sheeting and other protective materials when creating high-performance containment systems; Use for restoration, abatement and remodeling tasks such as painting, cleaning, sanding, mold remediation, asbestos removal and more.



^LS=LINER SIDE; ^ES=EXPOSED SIDE



GG 200



**GOLF GRIP
RUBBER-BASED ADHESIVE
CREPE PAPER**

TENSILE (LBS/IN WIDTH)	23
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	50
THICKNESS WITHOUT LINER (MILS)	6.5
ELONGATION (%)	10
SERVICE TEMPERATURE RANGE (°F)	50 - 150
APPLICABLE STANDARDS*	-

For factory and clubhouse golf grip installation; Can also be used for mounting, holding, splicing, tabbing and fastening a variety of substrates when an aggressive, double-sided tape is required.

DP 380



**GENERAL PURPOSE GRADE
POLYESTER (PET) FILM
SOLVENT-BASED ACRYLIC ADHESIVE**

TENSILE (LBS/IN WIDTH)	15.5
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	60
THICKNESS WITHOUT LINER (MILS)	4.4
ELONGATION (%)	110
SERVICE TEMPERATURE RANGE (°F)	-20 - 257
APPLICABLE STANDARDS*	-

For mounting banners, light signs, window blinds, emblems and nameplates; Also used for long-term or permanent bonding and attachment applications, including POP displays and laminating materials.

DP 391



**PROFESSIONAL GRADE
POLYESTER (PET) FILM
SYNTHETIC RUBBER ADHESIVE**

TENSILE (LBS/IN WIDTH)	23
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	82
THICKNESS WITHOUT LINER (MILS)	3.7
ELONGATION (%)	100
SERVICE TEMPERATURE RANGE (°F)	32 - 230
APPLICABLE STANDARDS*	-

For mounting, bonding and fastening a wide variety of substrates, including low surface energy plastics and coatings; Used for trim, profile and extrusion mounting; Can be used in non-direct UV exposure applications, such as vinyl and painted window frames, that demand clean removal; Also used for mounting indoor window kits.

DF 642



**INDUSTRIAL GRADE
POLYESTER/COTTON BLEND CLOTH
SYNTHETIC RUBBER ADHESIVE**

TENSILE (LBS/IN WIDTH)	32
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	32
THICKNESS WITHOUT LINER (MILS)	12.0
ELONGATION (%)	8
SERVICE TEMPERATURE RANGE (°F)	50 - 225
APPLICABLE STANDARDS*	-

For carpet and pad installation at convention centers, arenas and hotels; Used for general purpose holding and mounting applications; Can also be used to hold signs and dispensers for POP merchandising.

TRANSFER ADHESIVE

TA 450



**GENERAL PURPOSE GRADE
RESISTS HUMIDITY, MOST SOLVENTS
ACRYLIC-BASED ADHESIVE**

ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	25
THICKNESS WITHOUT LINER (MILS)	1.6
SERVICE TEMPERATURE RANGE (°F)	-22 - 302
APPLICABLE STANDARDS*	-

For mounting, holding, joining and splicing various substrates, including paper, cardboard, textiles, plastics, leather, wood, glass and painted surfaces; For use on displays, POS, posters, etc.



TG 356



**PREMIUM PERFORMANCE GRADE
RESISTS HUMIDITY, MOST SOLVENTS
ACRYLIC-BASED ADHESIVE**

ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	32
THICKNESS WITHOUT LINER (MILS)	2.0
SERVICE TEMPERATURE RANGE (°F)	-60 - 250
APPLICABLE STANDARDS*	-

For mounting, holding, joining and splicing various substrates, including paper, cardboard, textiles, plastics, leather, wood, glass and painted surfaces; For use on displays, POS, posters, etc.; Use with an adhesive transfer gun to make almost any surface self-adhesive. Reverse wound on a 1-in I.D. core.



DISPENSER

SD 950



**ADHESIVE TRANSFER GUN
PISTOL-GRIP
EASY TO LOAD**

For use with reverse wound adhesive transfer tape to quickly and easily make almost any surface self-adhesive; For mounting, holding, joining and splicing paper, cardboard, plastics, wood, leather, glass and painted surfaces; Can also be used when gift wrapping; For use with 0.75 in maximum width rolls.

RECOMMENDED PRODUCTS
TG 356



SHURTAPE INNOVATIONS

New or reinvented products that stay **TRUE TO YOUR WORK**

AF 100 with EasyPEEL UL 181A-P/B-FX LISTED TAPE



Page 41

PC 460 SHURGRIP® CO-EXTRUDED DUCT TAPE



Page 29

T-REX® SUPER PERFORMANCE TAPE



Page 32

PC 589 SHURGRIP® CO-EXTRUDED DUCT TAPE



Page 29

DS 154 DOUBLE-COATED PAPER TAPE



Page 46

PC 593 SHURGRIP® CO-EXTRUDED DUCT TAPE



Page 29

FP 115 FLATBACK PAPER TAPE



Page 9

PC 599 SHURGRIP® CO-EXTRUDED DUCT TAPE



Page 29

APPLICABLE STANDARDS

1	AMS-T-21595	19	CID A-A-1689B, Type I, Class 2
2	ANSI No. 45.2.2	20	CID A-A-1689B, Type II
3	ASME NQA-1	21	CID A-A-180C, Type II, Grade A
4	ASTM D 1974-98 (2003)	22	CID A-A-180C, Type II, Grade B
5	ASTM D-4236	23	CID A-A-55809
6	ASTM D 5330, Type II	24	FDA Indirect Contact CFR 21, 174.5
7	ASTM D 5486M-12, Type I, Class 2	25	FDA Indirect Contact CFR 21, 175.105
8	ASTM D 5486M-12, Type II, Class 2	26	FDA Indirect Contact CFR 21, 176.170
9	ASTM D 5486M-12, Type III	27	FDA Indirect Contact CFR 21, 176.180
10	ASTM D 5486M-12, Type IV	28	FDA Indirect Contact CFR 21, 177.1520
11	ASTM D 5486M-12, Type V	29	FDA Indirect Contact CFR 21, 177.1630
12	ASTM D 6123/D 6123M-97 (2012), Type I	30	FSI 0/SDI 0
13	ASTM D 6123/D 6123M-97 (2012), Type II	31	FSI 0/SDI 5
14	ASTM E 2072	32	FSI 0/SDI 10
15	CCMC Report No.: 13401-R	33	FSI 5/SDI 0
16	CID A-A-113D, Type I, Class A	34	FSI 5/SDI 5
17	CID A-A-1586A	35	FSI 5/SDI 10
18	CID A-A-1684C	36	FSI 10/SDI 10

37	FSI 15/SDI 20
38	FSI 15/SDI 25
39	FSI 15/SDI 30
40	FSI 15/SDI 40
41	FSI 20/SDI 40
42	FSI 25/SDI 50
43	L-T-80B
44	MIL-STD-2041D
45	MIL-T-23397C
46	NRC Guide 1.38
47	Pressure Classes SMACNA 1/2, 1, 2, 3, 4 & 6
48	SAE-AMS-T-23397
49	Seal Classes A, B, C
50	UL 181A-P
51	UL 181B-FX
52	UL 723
53	UL Listed

PRODUCT INDEX

AF 75	42	CP 400	7	FrogTape®	4	P- 68	34	PC 626	30	SD 936	22
AF 100	41	CP 450	7	GG 200	46	P- 628	34	PC 629	31	SD 937	23
AF 912	42	CP 500	7	GP 100	20	P- 660	34	PC 657®	32	SD 950	48
AF 914CT	41	CP 631	8	GS 490	19	P- 661	34	PC 658	32	SD 955	23
AF 973	42	CP 650	7	GS 496	14	P- 665®	35	PC 667	36	SD 999	22
AF 975CT	41	CP 743	6	GS 500	19	P- 670	35	PC 668	36	SF 682	31
AF 982	42	CP 905	7	GS 501	19	P- 672®	34	PC 721	32	SF 683	31
AF 984CT	41	CT 109	17	GS 521	19	P- 691®	34	PC 857	40	SF 685	40
AF 990CT	41	DC 181	40	GS 531	19	PC 460	29	PC 858CA	40	SF 686	40
AP 15	17	DF 63	46	HP 100®	12	PC 567	36	PE 100	6	SP 222	23
AP 101®	15	DF 65	46	HP 132®	13	PC 589	29	PE 333	37	SP 7000	25
AP 180®	15	DF 545	47	HP 200®	12	PC 590	28	PE 444	37	SP 8000	25
AP 201®	15	DF 642	47	HP 232®	13	PC 593	29	PE 555	37	T-REX®	32
AP 301®	15	DP 380	47	HP 235	13	PC 595	28	PP 802	16	TA 450	48
AP 401®	15	DP 391	47	HP 240	14	PC 599	29	PP 803	16	TG 356	48
BT 100	43	DP 401	47	HP 250	14	PC 600C	30	PP 807	17	VF 719	17
CF 740	7	DS 154	46	HP 260	14	PC 600S	28	PP 808	17	VP 410	43
COLONIAL®	5	DT 200	46	HP 300®	12	PC 609	31	PP 810	16	VP 415	43
CP 27®	4	EM 101	4	HP 400®	12	PC 610	31	PP 815	16	WP 100	20
CP 60®	4	EV 57B	43	HP 460	14	PC 618C	30	PS 748	18	WP 200	20
CP 66®	5	FP 17	8	HP 500®	12	PC 618S	28	PS 750	18	WP 300	20
CP 83	6	FP 96	9	HP 560	14	PC 619	30	PW 100	43	WP 400	20
CP 101	6	FP 97	9	HP 800	12	PC 621	32	SD 930	22		
CP 102	5	FP 115	9	HW 300	42	PC 622	36	SD 931	23		
CP 105	6	FP 202	9	IT 100	43	PC 623	33	SD 932	22		
CP 107	5	FP 227	8	JLAR	16	PC 624	33	SD 934	22		
CP 150	4	FP 726	8	LS 300	42	PC 625	33	SD 935	22		

LOCATIONS

U.S. CORPORATE HEADQUARTERS

Shurtape Technologies, LLC
 1712 8th Street Drive SE
 Hickory, NC 28602 USA
 Phone: (828) 322-2700
 (888) 442-8273
 Fax: (828) 322-4029
 Email: custservice@shurtape.com
 Website: www.shurtape.com

SHURTECH BRANDS, LLC

32150 Just Imagine Drive
 Avon, OH 44011 USA
 Phone: (440) 937-7000
 (800) 321-1733
 Fax: (440) 937-7077

MEXICO

Shurtape México, S. de R.L. de C.V.
 Paseo de la Constitución #11
 Fracc. Ind. Peñuelas
 CP 76148, Queretaro, Qro. México
 Phone: +52 (442) 220-6367
 Fax: +52 (442) 220-6366
 Email: pmartinez@shurtapemexico.com

SOUTH AMERICA

Shurtape Perú S.A.
 Calle Minería 141
 Santa Anita, Lima 43
 Perú
 Phone: +51 (1) 416-3400
 Fax: +51 (1) 383-0476
 Email: ventas@shurtapeperu.com
 Website: www.shurtapeperu.com

UNITED KINGDOM

Shurtape UK Ltd.
 39 Mark Road
 Hemel Hempstead
 Hertfordshire, HP2 7DN UK
 Phone: +44 (0)1442 275312
 Fax: +44 (0)1442 275301
 Email: info@shurtapeuk.com
 Website: www.shurtape.co.uk

EUROPE

Kip GmbH
 Schlavenhorst 9 (Industriepark)
 D-46395 Bocholt, Germany
 Phone: +49 2871-23466-2327
 Fax: +49 2871-23466-2332
 Email: export@kip-tape.com
 Website: www.kip-tape.com

MIDDLE EAST

Shurtape Ved Ltd.
 Jebel Ali Free Zone,
 Dubai, United Arab Emirates
 Phone: +971 (4) 881-3155
 Fax: +971 (4) 881-3166
 Fax: +971 (4) 883-1974
 Email: shurtape@emirates.net.ae

ASIA

Shurtape Technologies (Changshu) Co. Ltd.
 Changshu Southeast Economic
 Development Zone
 No.301 Yintong Road
 Jiangsu, China 215500
 Phone: +86 (512) 5235-9500
 Fax: +86 (512) 5235-9528
 Email: info@shurtape.com.cn

UNITED STATES DISTRIBUTION CENTERS

North Carolina
 3389 Catawba Industrial Place
 Catawba, NC 28609 USA
 Phone: (828) 322-2700
 (888) 442-8273

Arizona

First Commerce Center
 725 N 73rd Avenue, Suite 112
 Phoenix, AZ 85043 USA
 Phone: (623) 463-5886
 (800) 342-8273
 Fax: (623) 463-5809

Oklahoma

4800 Partnership Drive
 Oklahoma City, OK 73131
 Phone: (405) 475-0202
 Fax: (405) 475-0211

Ontario, Canada

6685 Kennedy Rd. Suite 3
 Mississauga, ON
 Canada L5T 3A5
 Phone: (905) 696-0800
 Fax: (905) 696-8176

WARRANTY INFORMATION

Shurtape Technologies, LLC, guarantees its products to be in compliance with acceptable standards for material and workmanship, but limits its obligation under this warranty to replacement or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Shurtape Technologies, LLC. Shurtape Technologies, LLC, neither makes nor authorizes, nor shall be bound to any other warranty of merchantability, and under no circumstances will it be liable for any loss, damage, expense or consequential damage or loss of any kind either in tort or contract, arising directly or indirectly out of or in connection with the use of or inability to use its products.

Product literature, specifications, product and test reports, and other descriptive and advertising material and information are based on research testing and are believed to be reliable but constitute no part of this warranty, which is exclusively and strictly limited to the foregoing. Shurtape products are sold on the understanding that the buyer has determined or will determine the suitability of the product for buyer's purposes, and is reminded that some materials are sensitive to adhesive-based products and discretion should be used in their application.

No agent or representative is authorized to give any guarantee or make any statement contrary to or inconsistent with this warranty.

All trademarks listed are the property of Shurtape Technologies, LLC, unless otherwise noted.





Shurtape®

TRUE TO YOUR WORK™

Shurtape Technologies, LLC
P. O. Box 1530
Hickory, NC 28603-1530 USA

Shurtape.com
1.888.442.TAPE
custservice@shurtape.com

ISO 9001-CERTIFIED QUALITY SYSTEM